

# SRS Getriebefluid 5 L



## Fully Synthetic Manual Transmission Oil

February 2019

### Characteristics

**SRS Getriebefluid 5L** is fully synthetic gear oil with tailor made additives to fulfil the requirements of manual transmissions. It is designed for both perfect synchronisation function and high wear protection. The viscosity of SAE 75W-90 reduces stiffness at low temperatures, particularly in 5-speed gear boxes. At the same time its distinctive high temperature viscosity prevents noise at high operating temperatures.

### Application

**SRS Getriebefluid 5 L** is suitable for use in all passenger car transaxle blocks with longitudinally mounted gear boxes. The hypoid gears with minor axle offsets which are usually used in these gear boxes are also effectively protected through its high wear protection

### Specifications

- SAE Grade 75W-90
- API GL-4 plus

### Recommendations

- VW 501 50

SRS Getriebefluid 5 L is a product of the H&R ChemPharm GmbH.

Typical Data		Test Method	SRS Getriebefluid 5 L
SAE Grade		SAE J 306	75W-90
Density at 15°C	g/cm <sup>3</sup>	DIN 51 757	0.850
Dyn. Viscosity at -40°C	mPa s	DIN 51 398	29,700
Kin. Viscosity at 40°C	mm <sup>2</sup> /s	DIN EN ISO 3104	88.3
Kin. Viscosity at 100°C	mm <sup>2</sup> /s	DIN EN ISO 3104	15.1
Viscosity Index (VI)		DIN ISO 2909	180
Flash Point COC		DIN ISO 2592	212
Pour Point		DIN ISO 3016	-61

The above values may vary within the commercial limits.

**Made in Germany**