

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 1 of 18

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

engine oil

### Uses advised against

No information available.

# 1.3. Details of the supplier of the safety data sheet

Company name: SRS Schmierstoff Vertrieb GmbH

Street: Neuenkirchener Straße 8
Place: D-48497 Salzbergen
Telephone: 05976 - 945-0

Responsible Department: Abt. Produktsicherheit: info.reach@srs-oil.de

1.4. Emergency telephone Gift-Informationszentrum Nord (Göttingen) - Telefon 0551-19240

number:

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Regulation (EC) No 1272/2008

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

### Regulation (EC) No 1272/2008

# **Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

# **Precautionary statements**

P273 Avoid release to the environment.

P501 Dispose of contents/container to local/regional/national/international regulations.

### Special labelling of certain mixtures

EUH208 Contains C14-18 alpha-olefin epoxide, reaction products with boric acid, triphenyl phosphite,

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate. May

produce an allergic reaction.

### 2.3. Other hazards

Endocrine disrupting properties: phenol, dodecyl-, branched. For information or further instructions, see also section 11 or 12.

phenol, dodecyl-, branched: This substance has been listed as SVHC (substance of very high concern) in the Candidate List according to Article 59 of REACH.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

### Relevant ingredients

CAS No	Chemical name	Quantity	ı
--------	---------------	----------	---



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 2 of 18

	EC No	Index No	REACH No	
	Classification (Regulation (EC)	No 1272/2008)	•	
64742-54-7	Distillates (petroleum), hydrotre	35 - < 40 %		
	265-157-1	649-467-00-8	01-2119484627-25	
	Asp. Tox. 1; H304	,	·	
157707-86-3	Dec-1-ene, trimers, hydrogenat	ed		30 - < 35 %
	500-183-1		01-2119486452-34	
	Asp. Tox. 1; H304	•		
	Mineral Oil* (64742-54-7, 64742	2-65-0, 64742-55-8, 64742-56-9	))	5 - < 7 %
	Asp. Tox. 1; H304			
	Mineral Oil* (64742-54-7, 64742	2-65-0, 64742-56-9)		5 - < 7 %
	Asp. Tox. 1; H304			
4259-15-8	zinc bis[O,O-bis(2-ethylhexyl)] b	ois(dithiophosphate)		1 - < 3 %
	224-235-5		01-2119493635-27	
	Eye Dam. 1, Aquatic Chronic 2;			
	Calcium branched alkyl phenate	1 - < 3 %		
	Aquatic Chronic 4; H413			
1471314-23- 4	C14-18 alpha-olefin epoxide, re	0.5 - < 1 %		
	939-580-3		01-2119976364-28	
	Skin Sens. 1B; H317		•	
75975-85-8	Benzene, polypropene derivativ	0.5 - < 1 %		
	Skin Sens. 1B; H317			
27859-58-1	(tetrapropenyl)succinic acid			0.1 - < 0.2 %
	248-698-8		01-2120752504-57	
	Repr. 2, Skin Irrit. 2, Eye Dam.	1, STOT RE 2; H361 H315 H31	8 H373	
101-02-0	triphenyl phosphite			0.1 - < 0.2 %
	202-908-4	015-105-00-7	01-2119511213-58	
	Acute Tox. 4, Skin Irrit. 2, Eye II H319 H317 H400 H410	rit. 2, Skin Sens. 1, Aquatic Ac	ute 1, Aquatic Chronic 1; H302 H315	
80-62-6	methyl methacrylate; methyl 2-r	methylpropenoate**	0.1 - < 0.2 %	
	201-297-1			
	Flam. Liq. 2, Skin Irrit. 2, Skin S			
121158-58-5	phenol, dodecyl-, branched			< 0.1 %
	310-154-3	604-092-00-9	01-2119513207-49	
	Repr. 1B, Skin Corr. 1C, Eye Da H400 H410			

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity					
	Specific Conc. I	pecific Conc. Limits, M-factors and ATE						
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified						
	dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg							
157707-86-3	500-183-1	500-183-1 Dec-1-ene, trimers, hydrogenated						
	inhalation: LC50 = >5,2 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg							



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

#### SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 3 of 18

4259-15-8	224-235-5	zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	1 - < 3 %			
	dermal: LD50 = Eye Irrit. 2; H31	= > 5000 mg/kg; oral: LD50 = > 3100 mg/kg				
1471314-23- 4	939-580-3	C14-18 alpha-olefin epoxide, reaction products with boric acid	0.5 - < 1 %			
	dermal: LD50 =	= >2000 mg/kg; oral: LD50 = >16000 mg/kg				
75975-85-8		Benzene, polypropene derivatives, sulfonated, calcium salts	0.5 - < 1 %			
	Skin Sens. 1B;	H317: >= 10 - 100				
27859-58-1	248-698-8	(tetrapropenyl)succinic acid	0.1 - < 0.2 %			
	oral: LD50 = 2°	100 mg/kg				
101-02-0	202-908-4	triphenyl phosphite	0.1 - < 0.2 %			
		60 = >6,7 mg/l (dusts or mists); dermal: LD50 = >2000<5000 mg/kg; oral: ATE = in Irrit. 2; H315: >= 5 - 100				
80-62-6	201-297-1	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**	0.1 - < 0.2 %			
	inhalation: LC50 = 29,8 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 8400 mg/kg					
121158-58-5	310-154-3	phenol, dodecyl-, branched	< 0.1 %			
		= 15000 mg/kg; oral: LD50 = 2100 mg/kg   Aquatic Acute 1; H400: M=10 c 1; H410: M=10				

#### **Further Information**

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London).

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

# After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, seek medical treatment.

## After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

# After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

<sup>\*\*</sup>Substance for which a community occupational exposure limit value applies in the European Union.

<sup>\*</sup>The mineral oil can be described by one or more EINECS numbers. 265-157-1, 265-169-7, 265-158-7, 265-159-2, (REACH-no.: 01-2119484627-25, 01-2119471299-27, 01-2119487077-29, 01-2119480132-48)



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

#### SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 4 of 18

### 4.2. Most important symptoms and effects, both acute and delayed

If swallowed or in the event of vomiting, risk of entering the lungs.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Sand. Foam. Carbon dioxide (CO2). Extinguishing powder. In case of major fire and large quantities: Water spray jet. Water mist.

### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO2) Sulphur dioxide (SO2) Nitrogen oxides (NOx)

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Co-ordinate fire-fighting measures to the fire surroundings.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Ventilate affected area.

Special danger of slipping by leaking/spilling product.

# For non-emergency personnel

Wear personal protection equipment (refer to section 8).

#### For emergency responders

No special measures are necessary.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil. If required, notify relevant authorities according to all applicable regulations.

### 6.3. Methods and material for containment and cleaning up

#### For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

No information available.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 5 of 18

### Advice on safe handling

Wear suitable protective clothing. ( See section 8. )

Avoid formation of oil dust.

### Advice on protection against fire and explosion

Usual measures for fire prevention. Keep away from sources of ignition - No smoking.

Fire class B

### Advice on general occupational hygiene

Clean skin thoroughly after working.

Do not put any product-impregnated cleaning rags into your trouser pockets.

Contaminated work clothing should not be allowed out of the workplace.

Wash contaminated clothing before reuse.

### Further information on handling

Do not breathe vapour/aerosol.

Avoid contact with eyes and skin.

General protection and hygiene measures: See section 8.

# 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

### Hints on joint storage

Do not store together with: Gas. Explosives. Oxidizing substances. Radioactive substances. Infectious substances

### Further information on storage conditions

Temperature control required. Protect from light. Keep container tightly closed. Do not allow contact with air.

# 7.3. Specific end use(s)

See section 1.

### **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m³	fib/cm³	Category	Origin
80-62-6	Methyl methacrylate	50	-		TWA (8 h)	
		100	-		STEL (15 min)	

# **DNEL/DMEL values**

CAS No	Name of agent						
DNEL type		Exposure route	Effect	Value			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Base	oil - unspecified					
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m³			
Worker DNEL,	Worker DNEL, long-term		local	5,58 mg/m³			
Worker DNEL,	Worker DNEL, long-term		systemic	0,97 mg/kg bw/day			
Consumer DNEL, long-term		inhalation	local	1,19 mg/m³			
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day			



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 6 of 18

Worker DNEL, long-term	inhalation	systemic	6,6 mg/m³
Worker DNEL, long-term	dermal	systemic	9,6 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	1,67 mg/m³
Consumer DNEL, long-term	dermal	systemic	4,8 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,19 mg/kg bw/day
1471314-23- C14-18 alpha-olefin epoxide, reaction products w	ith boric acid		
Worker DNEL, long-term	dermal	local	0,09 mg/cm <sup>2</sup>
Consumer DNEL, long-term	dermal	local	4,68 mg/cm <sup>2</sup>
27859-58-1 (tetrapropenyl)succinic acid			
Worker DNEL, long-term	inhalation	systemic	1,2 mg/m³
Worker DNEL, long-term	dermal	systemic	0,7 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,3 mg/m³
Consumer DNEL, long-term	dermal	systemic	0,3 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,2 mg/kg bw/day
101-02-0 triphenyl phosphite			
Worker DNEL, long-term	inhalation	systemic	0,53 mg/m³
Worker DNEL, long-term	dermal	systemic	0,15 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,53 mg/m³
Consumer DNEL, long-term	dermal	systemic	0,15 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,075 mg/kg bw/day
121158-58-5 phenol, dodecyl-, branched			
Worker DNEL, acute	inhalation	systemic	44,18 mg/m³
Worker DNEL, acute	dermal	systemic	166 mg/kg bw/day
Consumer DNEL, acute	inhalation	systemic	13,26 mg/m³
Consumer DNEL, acute	dermal	systemic	50 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	1,26 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	1.762 mg/m³
Worker DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,79 mg/m³
Consumer DNEL, long-term	dermal	systemic	0,075 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,075 mg/kg bw/day

# PNEC values

CAS No	Name of agent					
Environmental compartment Value						
64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified						
Secondary poisoning 9,33 mg						
4259-15-8 zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)						



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 7 of 18

Freshwater	0,004 mg/l
Freshwater (intermittent releases)	0,044 mg/l
Marine water	0,0046 mg/l
Freshwater sediment	0,322 mg/l
Secondary poisoning	8,33 mg/kg
Micro-organisms in sewage treatment plants (STP)	0,038 mg/l
Soil	0,062 mg/kg
1471314-23- C14-18 alpha-olefin epoxide, reaction products with boric acid	
Freshwater	1 mg/l
Marine water	0,1 mg/l
Freshwater sediment	42700 mg/kg
Marine sediment	4270 mg/kg
Micro-organisms in sewage treatment plants (STP)	100 mg/l
Soil	8540 mg/kg
27859-58-1 (tetrapropenyl)succinic acid	
Freshwater	0,1 mg/l
Freshwater (intermittent releases)	1 mg/l
Marine water	0,01 mg/l
Freshwater sediment	62,1 mg/kg
Marine sediment	6,21 mg/kg
Secondary poisoning	3,33 mg/kg
Micro-organisms in sewage treatment plants (STP)	100 mg/l
Soil	12,4 mg/kg
121158-58-5 phenol, dodecyl-, branched	
Freshwater	0,000074 mg/l
Freshwater (intermittent releases)	0,00037 mg/l
Marine water	0,000007 mg/l
Freshwater sediment	0,226 mg/kg
Marine sediment	0,027 mg/kg
Secondary poisoning	4 mg/kg
Micro-organisms in sewage treatment plants (STP)	100 mg/l
Soil	0,118 mg/kg

# Additional advice on limit values

Air limit values:

Possibility of exposure to Aerosol (Mineral oil ) Limit value (TLV-TWA ) = 5 mg/ m3 - Source: ACGIH Limit value (TLV-STEL ) = 10 mg/ m3 - Source: ACGIH

STEL: short-term exposure limits TLV: Threshold Limiting Value TWA: time weighted average

ACGIH:American Conference of Governmental Industrial Hygienists

# 8.2. Exposure controls



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

#### SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 8 of 18







## Appropriate engineering controls

Provide adequate ventilation.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Safety goggles with side protection. In case of increased risk add protective face shield. EN 166

#### Hand protection

Use safety gloves of following materials: NBR (nitrile) / neopren / viton (permeationslevel 5 - 6), Cat. II according to norm EN 374/EN 388.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Gloves must be periodically inspected and changed in case of wear, perforations or contaminations.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

#### Skin protection

Oil-resistant and hardly inflammable protective clothing.

### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

- -aerosol or mist formation
- -Exceeding exposure limit values

Suitable respiratory protection apparatus: Respiratory equipment in case of nebulosity or aerosol: Use a mask with a filter type A2, A2/P2 or ABEK.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

#### **Environmental exposure controls**

No information available.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: clear

Odour: characteristic

Test method

Print date: 13.05.2024

Melting point/freezing point:

Boiling point or initial boiling point and

No information available.

No information available.

boiling range:

Flammability:

Lower explosion limits:

Upper explosion limits:

No information available.

No information available.

No information available.

Flash point: 237 °C DIN ISO 2592

Auto-ignition temperature:

Decomposition temperature:

No information available.

PH-Value:

No information available.

No information available.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 9 of 18

Viscosity / kinematic: 53,96 mm²/s DIN EN ISO 3104

(at 40 °C)

Water solubility:

No information available.

Solubility in other solvents

No information available.

No information available.

Partition coefficient n-octanol/water: No information available.

Vapour pressure: <0,1 hPa calculated.

(at 20 °C)

Vapour pressure: No information available.

(at 50 °C)

Density (at 15 °C): 0,8597 g/cm³ DIN 51757

Bulk density:

Relative vapour density:

No information available.

No information available.

No information available.

No information available.

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

nono ' '

Sustaining combustion:

No data available

Self-ignition temperature

Solid: No information available.

Gas: No information available.

Oxidizing properties

none

Other safety characteristics

Evaporation rate:

Solvent separation test:

No information available.

Solvent content:

No information available.

No information available.

No information available.

No information available.

Sublimation point:

No information available.

No information available.

No information available.

Pour point: -51 °C ISO 3016

Viscosity / dynamic:

No information available.

No information available.

**SECTION 10: Stability and reactivity** 

10.1. Reactivity

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

Refer to chapter 10.5.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 10 of 18

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

# Toxicocinetics, metabolism and distribution

No information available.

### **Acute toxicity**

Based on available data, the classification criteria are not met.

### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified								
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier	OECD 401			
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier	OECD 402			
157707-86-3	Dec-1-ene, trimers, h	ydrogenated							
	oral	LD50 mg/kg	>5000	Rat.	ECHA Dossier				
	dermal	LD50 mg/kg	>2000	Rat.	ECHA Dossier				
	inhalation (4 h) dust/mist	LC50	>5,2 mg/l	Rat.	ECHA Dossier	OECD 403			
4259-15-8	zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)								
	oral	LD50 mg/kg	> 3100	Rat.	ECHA Dossier				
	dermal	LD50 mg/kg	> 5000	Rabbit.	ECHA Dossier				
1471314-23- 4	C14-18 alpha-olefin epoxide, reaction products with boric acid								
	oral	LD50 mg/kg	>16000	Rat	ECHA Dossier				
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier				
27859-58-1	(tetrapropenyl)succini	ic acid							
	oral	LD50 mg/kg	2100	Rat	ECHA Dossier	OECD Guideline 401			
101-02-0	triphenyl phosphite								
	oral	ATE mg/kg	500						
	dermal	LD50 000 mg/kg	>2000<5	Rabbit	REACH Dossier	OECD 402			
	inhalation (1 h) dust/mist	LC50	>6,7 mg/l	Rat	REACH Dossier	OECD 403			
80-62-6	methyl methacrylate;	methyl 2-methy	Iprop-2-enoa	te; methyl 2-methy	ylpropenoate**				



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 11 of 18

	oral	LD50 mg/kg	8400	Rat		
	dermal	LD50 mg/kg	> 5000	Rabbit	ECHA Dossier	
	inhalation (4 h) dust/mist	LC50	29,8 mg/l	Rat	ECHA Dossier	
121158-58-5	phenol, dodecyl-, branche	ed				
	oral	LD50 mg/kg	2100	Rat	ECHA Dossier	OECD 401
	dermal	LD50 mg/kg	15000	Rabbit	ECHA Dossier	OECD 402

#### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate):

Eye Dam. 1: SCL > 50%

Eye Irrit. 2: SCL > 50% (Source: Manufacturer)

### Sensitising effects

Based on available data, the classification criteria are not met.

Contains C14-18 alpha-olefin epoxide, reaction products with boric acid, triphenyl phosphite, methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate. May produce an allergic reaction. May cause sensitisation especially in sensitive humans.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified:

In vitro mutagenicity/genotoxicity Method: OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test); Result: negative Literature information: REACH Dossier; Carcinogenicity: Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies); Species: Mouse.; Results: Non-carcinogenic if DMSO extract as measured by IP346 is less than 3% m/m. Literature information: REACH Dossier; Reproductive toxicity: Species: Rat (Sprague-Dawley); Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test); Results: NOAEL > 1000 mg/kg Literature information: REACH Dossier; Developmental toxicity/teratogenicity: Species: Rat (Sprague-Dawley); Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Results: NOAEL >= 2000 mg/kg Literature information: REACH Dossier

## Dec-1-ene, trimers, hydrogenated:

In vitro mutagenicity/genotoxicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative Literature information: REACH Dossier; Reproductive toxicity: Species: Rat; Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test); Result: NOAEL > 1000 mg/kg; Literature information: REACH Dossier

# zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate):

In vitro mutagenicity/genotoxicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative Literature information: REACH Dossier; Developmental toxicity/teratogenicity/Reproductive toxicity:; Species: Rat (Sprague-Dawley); Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test); Result: NOAEL = 30 mg/kg; Literature information: REACH Dossier

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate:

In-vitro mutagenicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative Literature information: REACH Dossier; Carcinogenicity: Method: (inhalation.): OECD Guideline 451



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

#### SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 12 of 18

(Carcinogenicity Studies, 6h/d); Species: Mouse.; Exposure duration: 2 years; Result: NOAEC = 4,1 mg/l; Literature information: REACH Dossier; Reproductive toxicity: Method: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study); Species: Rat; Result: NOAEL = 400 mg/kg; Literature information: REACH Dossier; Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Species: Rabbit.

Exposure duration: 28d; Result: NOAEL = 450 mg/kg; Literature information: REACH Dossier

#### triphenyl phosphite:

In-vitro mutagenicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Literature information: REACH Dossier; Result: negative; Reproductive toxicity: Species: Rat (Wistar); Method: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test); Exposure time: 112d; Results: NOAEL 40 mg/kg; Literature information: REACH Dossier; Developmental toxicity/teratogenicity: Species: Rabbit.; Method: OECD 422; Results: NOAEL 15 mg/kg; Literature information: REACH Dossier

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified:

Subacute inhalative toxicity: Method: -; Exposure time: 28d; Species: Rat; Results: NOAEL >980 mg/m3; Literature information: REACH Dossier; Subacute dermal toxicity: Method: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study); Exposure time: 28d; Species: Rabbit; Results: 1000 mg/kg; Literature

information: REACH Dossier

Dec-1-ene, trimers, hydrogenated:

Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Species: Rat; Results: NOAEL 1000 mg/kg; Literature information: REACH Dossier

zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate):

Subacute oral toxicity: Method: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents);

Species: Rat; Results: NOAEL = 125 mg/kg; Literature information: REACH Dossier

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate:

Chronic oral toxicity: Method: -; Species: Rat; Exposure duration: 2 years; Results: NOAEL = 2000 ppm. Literature information: REACH Dossier; Chronic inhalation toxicity: Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies, 6h/d); Species: Rat; Exposure duration: approx. 2 years; Results: LOAEC = 250 ppm. Literature information: REACH Dossier

### triphenyl phosphite:

Chronic oral toxicity: Method: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test); Exposure time: 112d; Species: Rat; Results: NOAEL 15 mg/kg

# **Aspiration hazard**

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

### **Endocrine disrupting properties**

Endocrine disrupting properties: phenol, dodecyl-, branched.

### Other information

Frequently or prolonged contact with skin may cause dermal irritation.

# **SECTION 12: Ecological information**



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 13 of 18

### **12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

If this product contains phenol, dodecyl, branched (EC No. 310-154-3), this product is not to be classified as dangerous for the environment. Raw materials containing this substance have not been classified by our suppliers as hazardous to the environment on the basis of test data, expert judgement or analogy assessments.

CAS No	No Chemical name									
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method			
64742-54-7	Distillates (petroleum), hy	drotreated he	eavy paraffir	nic; Base	oil - unspecified					
	Crustacea toxicity	NOEC	10 mg/l	21 d	Daphnia magna (OECD 211)	ECHA Dossier				
157707-86- 3	Dec-1-ene, trimers, hydrogenated									
	Acute fish toxicity	LL50 mg/l	>1000	96 h	Pimephales promelas	ECHA Dossier	USEPA (1975)			
	Acute crustacea toxicity	EL50 mg/l	>1000	48 h	Daphnia magna	ECHA Dossier	OECD Guideline 202			
	Crustacea toxicity	NOEC	125 mg/l	21 d	Daphnia magna	ECHA Dossier	OECD Guideline 211			
4259-15-8	zinc bis[O,O-bis(2-ethylhe	exyl)] bis(dithi	ophosphate	;)						
	Acute fish toxicity	LC50	46 mg/l	96 h	Cyprinodon variegatus	ECHA Dossier				
1471314-23 -4	C14-18 alpha-olefin epoxi	de, reaction	products wit	th boric a	icid					
	Acute fish toxicity	LC50 100 mg/l	LL50 >	96 h	Oncorhynchus mykiss	ECHA Dossier				
	Acute algae toxicity	ErC50 >100 mg/l	EL50	72 h	Pseudokirchneriella subcapitata	ECHA Dossier				
	Acute crustacea toxicity	EC50 >100 mg/l	EL50	48 h	Daphnia magna	ECHA Dossier				
	Crustacea toxicity	NOEC	10 mg/l	21 d	Daphnia magna	ECHA Dossier				
27859-58-1	(tetrapropenyl)succinic ac	id								
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Oncorhynchus mykiss	ECHA Dossier	OECD Guideline 203			
	Acute algae toxicity	ErC50	100 mg/l	96 h	Pseudokirchneriella subcapitata	ECHA Dossier	OECD Guideline 201			
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	ECHA Dossier	OECD Guideline 202			
80-62-6	methyl methacrylate; meth	hyl 2-methylp	rop-2-enoat	te; methy	/l 2-methylpropenoate**					
	Acute fish toxicity	LC50	410 mg/l	96 h	Pimephales promelas	ECHA Dossier				
	Acute algae toxicity	ErC50 mg/l	>110	72 h	Pseudokirchnerella subcapitata (OECD 201)	ECHA Dossier				
	Acute crustacea toxicity	EC50	720 mg/l	48 h	Daphnia magna	ECHA Dossier				
121158-58- 5	phenol, dodecyl-, branche	ed								
	Acute fish toxicity	LC50 40 mg/l	EL 50 =	96 h	Pimephales promelas	ECHA Dossier				
	•			•		•	•			



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 14 of 18

Acute algae toxicity	ErC50 mg/l	(0,36)		Desmodesmus subspicatus	ECHA Dossier	
Crustacea toxicity	NOEC mg/l	0,0037	21 d	daphnia magna	ECHA Dossier	OECD 211

# 12.2. Persistence and degradability

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation	,		•		
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	31%	28	ECHA Dossier		
	Not easily bio-degradable (according to OECD-criteria).					
	OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C	2-4%	28	ECHA Dossier		
	Not easily bio-degradable (according to OECD-criteria).					
157707-86-3	Dec-1-ene, trimers, hydrogenated					
	OECD 301D / EEC 92/69 annex V, C.4-E	2 %	28	ECHA Dossier		
	Not easily bio-degradable (according to OECD-criteria).					
4259-15-8	zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)					
	OECD 301D / EEC 92/69 annex V, C.4-E	< 5%	27	ECHA Dossier		
	Not easily bio-degradable (according to OECD-criteria).					
1471314-23- 4	C14-18 alpha-olefin epoxide, reaction products with boric acid					
	OECD Guideline 301 B	26,7%	28	ECHA Dossier		
	Not readily biodegradable (according to OECD criteria)					
27859-58-1	(tetrapropenyl)succinic acid					
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	18,3 %	28	ECHA Dossier		
	Not easily bio-degradable (according to OECD-criteria).					
101-02-0	triphenyl phosphite					
	OECD 301D / EEC 92/69 annex V, C.4-E	0,14%	28	REACH Dossier		
	Not readily biodegradable (according to OECD criteria)					
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**					
	OECD 301C / ISO 9408 / EWG 92/69 Anhang V, C.4-F	94%	14	ECHA Dossier		
	Readily biodegradable (according to OECD criteria).					
121158-58-5	phenol, dodecyl-, branched					
	OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C	25%	28	ECHA Dossier		
	Not easily bio-degradable (according to OECD-criteria).					

# 12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
157707-86-3	Dec-1-ene, trimers, hydrogenated	>6,5
4259-15-8	zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	3,59
1471314-23-4	C14-18 alpha-olefin epoxide, reaction products with boric acid	>= 6.24 - 9.4
27859-58-1	(tetrapropenyl)succinic acid	>= 3,286
101-02-0	triphenyl phosphite	6,62
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**	1,32
121158-58-5	phenol, dodecyl-, branched	7,1



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 15 of 18

#### BCF

CAS No	Chemical name	BCF	Species	Source
121158-58-5	phenol, dodecyl-, branched	2,9		

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

## 12.6. Endocrine disrupting properties

Endocrine disrupting properties: phenol, dodecyl-, branched.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

### 12.7. Other adverse effects

No information available.

#### **Further information**

Ozone depletion potential (ODP): No information available.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### Disposal recommendations

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE

CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances;

hazardous waste

#### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

# Inland waterways transport (ADN)

14.1. UN number or ID number: UN 9006

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es):914.4. Packing group:-Hazard label:-Classification code:M12

### Marine transport (IMDG)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 16 of 18

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation. 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. 14.4. Packing group:

14.5. Environmental hazards

**ENVIRONMENTALLY HAZARDOUS:** Nο

14.6. Special precautions for user

Informations for safe handling see chapter 7.

Informations for personal protective equipment see chapter 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

phenol, dodecyl-, branched

Restrictions on use (REACH, annex XVII):

Entry 30, Entry 75

Directive 2010/75/EU on industrial

emissions:

No information available.

Directive 2004/42/EC on VOC in paints

No information available.

and varnishes:

Information according to Directive

2012/18/EU (SEVESO III):

#### Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No (mixture): 3

Observe in addition any national regulations!

#### **National regulatory information**

**Employment restrictions:** Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Not subject to 2012/18/EU (SEVESO III)

Water hazard class (D): 2 - obviously hazardous to water

### **Additional information**

Regulation (EU) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals: not relevant

15.2 Chemical Safety Assessment not applicable.

### **SECTION 16: Other information**

### Changes

This data sheet contains changes from the previous version in section(s): 12,16.

Rev.: 1.0 - 16.04.2015



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

#### SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 17 of 18

Rev.: 1,1 - 27.04.2016 Rev.: 2,0 - 30.05.2017 Rev.: 3,0 - 27.06.2018 Rev.: 4,0 - 18.06.2019

Rev.: 5,0 - 23.07.2020; Changes in chapter: 3.2, 9.1, 11.1, 12.1, 15.1, 16

Rev.: 6,0 - 10.02.2021; Changes in chapter: 2.1, 3.2, 8.1, 11.1, 12.1, 12.2, 12.3, 15.1, 16

Rev.: 7,0 - 07.02.2022, Changes in chapter:, 2.3, 3.2, 6.1, 6.3, 8.1, 8.2, 11.2, 12.5, 12.6, 12.7, 15.1, 16

Rev.: 8,0 - 31.01.2023, Changes in chapter:, 2.3, 3.2, 9.1, 12.6, 16

Rev.: 8,1 - 16.10.2023, Changes in chapter: 2.2, 3.2, 8.1, 11.1, 11.2, 12.1, 12.2, 12.3, 12.7, 14, 15, 16

Rev.: 8.2 - 13.05.2024, Changes in chapter: 3.2, 11.1, 12.1, 12.2, 12.3, 16

### Abbreviations and acronyms

Flam. Liq: Flammable liquid Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation Skin Sens: Skin sensitisation Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect concentration

NTP: National Toxicology Program

N/A: not applicable

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail )

SVHC: substance of very high concern TRGS Technische Regeln fuerGefahrstoffe TSCA: Toxic Substances Control Act VOC: Volatile Organic Compounds WGK: Water Hazard Class (Germany)



H302

H304

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### SRS Leichtlauf-Motorenöl O-1178 / QB-B-0443

Revision date: 13.05.2024 Page 18 of 18

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

#### R

uatic Chronic 3; H412	Calculation method			
televant H and EUH statements (number and full text)				
H225 Highly	flammable liquid and vapour.			

Causes severe skin burns and eye damage. H314 H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Harmful if swallowed.

H360F May damage fertility.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life. H413

**EUH208** Contains C14-18 alpha-olefin epoxide, reaction products with boric acid, triphenyl phosphite.

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate. May

produce an allergic reaction.

### **Further Information**

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method. Environmental hazards: Calculation method. Physical hazards: On basis of test data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)