

SRS Rekord plus



High Performance Monograde Engine Oils

February 2021

Characteristics

SRS Rekord plus are special high performance monograde engine oils. The performance covers the requirements of MTU oil category 2, MAN M 3275-2 and MB-Sheet 228.2 for monograde engine oils.

Application

SRS Rekord plus is recommended for use in heavy duty marine engines with extended oil drain intervals. It is also suitable for use in diesel engines of agricultural and construction vehicles as well as of stationary industrial installations.

Specifications

- SAE Grade 30 and 40
- ACEA E7
- API CI-4

Approvals

- MTU MTL 5044 Type 2

Recommendations

- MB 228.2H
- MAN M 3275-2
- Allison C-4

SRS Rekord plus engine oils are products of the H&R ChemPharm GmbH.

| Typical Data | Test Method | SRS Rekord plus | |
|-------------------------|-----------------|-----------------|-------|
| | | 30 | 40 |
| SAE Grade | SAE J 300 | 30 | 40 |
| Density at 15°C | DIN 51 757 | 0.892 | 0.893 |
| Kin. Viscosity at 40°C | DIN EN ISO 3104 | 101 | 129 |
| Kin. Viscosity at 100°C | DIN EN ISO 3104 | 11.8 | 13.9 |
| Viscosity Index (VI) | DIN ISO 2909 | 107 | 105 |
| Flash Point COC | DIN ISO 2592 | 250 | 270 |
| Pour Point | DIN ISO 3016 | -30 | -27 |
| Total Base Number | DIN ISO 3771 | 10.8 | 10.8 |

The above values may vary within the commercial limits.

Made in Germany

