

according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SRS Wiolan HVX 68

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hydraulic fluids

Uses advised against

none

1.3. Details of the supplier of the safety data sheet

Company name: SRS Schmierstoff Vertrieb GmbH

Street: Neuenkirchener Straße 8
Place: D-48497 Salzbergen
Telephone: 05976 - 945-0

Responsible Department: Abt. Produktsicherheit: info.reach@srs-oil.de

1.4. Emergency telephone Gift-Informationszentrum Nord (Göttingen)

number: Telefon 0551-19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container to local/regional/national/international regulations.

2.3. Other hazards

This mixture contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

For information or further instructions, see also section 11 or 12.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

Note valle ingrediente						
CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No 1272/2008)					
64742-55-8	-8 Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified					
	265-158-7	649-468-00-3	01-2119487077-29			
	Asp. Tox. 1; H304					
128-39-2	2,6-di-tert-butylphenol					
	204-884-0		01-2119490822-33			



according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 2 of 14

	Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic 1; H315 H400 H410				
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*				
	201-297-1	607-035-00-6	01-2119452498-28		
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity					
	Specific Conc. Limits, M-factors and ATE							
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified						
	inhalation: LC50 = > 5,53 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg							
128-39-2	204-884-0	2,6-di-tert-butylphenol	0.2 - < 0.3 %					
	dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg							
80-62-6	201-297-1	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*	< 0.1 %					
inhalation: LC50 = 29,8 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = >5000 mg/kg								

Further Information

*Substance for which a community occupational exposure limit value applies in the European Union.

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

If swallowed or in the event of vomiting, risk of entering the lungs.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media





according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 3 of 14

Suitable extinguishing media

Sand. Foam. Carbon dioxide (CO2). Extinguishing powder. In case of major fire and large quantities: Water spray jet. Water mist.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO2) Sulphur dioxide (SO2) Nitrogen oxides (NOx)

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ventilate affected area.

Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Wear personal protection equipment (refer to section 8).

For emergency responders

No special precautionary measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil. If required, notify relevant authorities according to all applicable regulations.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

No information available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wear suitable protective clothing. (See section 8.)

Avoid formation of oil dust.

Advice on protection against fire and explosion

Usual measures for fire prevention. Keep away from sources of ignition - No smoking.

Fire class B

Advice on general occupational hygiene

Clean skin thoroughly after working.

Do not put any product-impregnated cleaning rags into your trouser pockets.



according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 4 of 14

Further information on handling

Do not breathe vapour/aerosol.

Avoid contact with eyes and skin.

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

Hints on joint storage

Do not store together with: Gas. Explosives. Oxidizing substances. Radioactive substances. Infectious substances

Further information on storage conditions

Temperature control required. Protect from light. Keep container tightly closed. Do not allow contact with air.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m³	fib/cm³	Category	Origin
80-62-6	Methyl methacrylate	50			TWA (8 h)	
		100	-		STEL (15 min)	

DNEL/DMEL values

CAS No	Name of agent						
DNEL type		Exposure route	Effect	Value			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil	- unspecified					
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³			
Worker DNEL,	long-term	inhalation	local	5,58 mg/m³			
Worker DNEL,	long-term	dermal	systemic	0,97 mg/kg bw/day			
Consumer DNE	EL, long-term	inhalation	local	1,19 mg/m³			
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day			
128-39-2	2,6-di-tert-butylphenol						
Worker DNEL,	long-term	dermal	systemic	11,25 mg/kg bw/day			
Worker DNEL,	long-term	inhalation	systemic	70,61 mg/m³			
Consumer DNE	EL, long-term	inhalation	systemic	20,9 mg/m³			
Consumer DNE	EL, long-term	oral	systemic	6,75 mg/kg bw/day			
Consumer DNEL, long-term		dermal	systemic	6,75 mg/kg bw/day			
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methy	l 2-methylpropenoate*					
Worker DNEL,	long-term	inhalation	systemic	348,4 mg/m³			
Worker DNEL,	long-term	inhalation	local	208 mg/m³			



according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 5 of 14

Worker DNEL, acute	inhalation	local	416 mg/m³
Worker DNEL, long-term	dermal	systemic	13,67 mg/kg bw/day
Worker DNEL, long-term	dermal	local	1,5 mg/cm²
Worker DNEL, acute	dermal	local	1,5 mg/cm²
Consumer DNEL, long-term	inhalation	systemic	74,3 mg/m³
Consumer DNEL, long-term	inhalation	local	104 mg/m³
Consumer DNEL, acute	inhalation	local	208 mg/m³
Consumer DNEL, long-term	dermal	systemic	8,2 mg/kg bw/day
Consumer DNEL, long-term	dermal	local	1,5 mg/cm²
Consumer DNEL, acute	dermal	local	1,5 mg/cm²
Consumer DNEL, long-term	oral	systemic	8,2 mg/kg bw/day

PNEC values

CAS No	Name of agent					
Environmental	compartment	Value				
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified					
Secondary poi	soning	9,33 mg/kg				
128-39-2	2,6-di-tert-butylphenol					
Freshwater		0.001 mg/l				
Freshwater (in	termittent releases)	0.004 mg/l				
Marine water		0.0001 mg/l				
Freshwater se	diment	0,317 mg/kg				
Marine sedime	0,0317					
Secondary poi	60 mg/kg					
Micro-organisr	ns in sewage treatment plants (STP)	10 mg/l				
Soil		0,679 mg/kg				
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*					
Freshwater		0,94 mg/l				
Freshwater (in	termittent releases)	0,94 mg/l				
Marine water		0,094 mg/l				
Freshwater se	10,2 mg/kg					
Marine sedime	0,102 mg/kg					
Micro-organism	ns in sewage treatment plants (STP)	10 mg/l				
Soil		1,48 mg/kg				

Additional advice on limit values

Air limit values:

Possibility of exposure to Aerosol (Mineral oil) Limit value (TLV-TWA) = 5 mg/ m3 - Source: ACGIH Limit value (TLV-STEL) = 10 mg/ m3 - Source: ACGIH

STEL: short-term exposure limits TLV: Threshold Limiting Value TWA: time weighted average

ACGIH:American Conference of Governmental Industrial Hygienists

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 6 of 14







Appropriate engineering controls

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety goggles with side protection. In case of increased risk add protective face shield. EN 166

Hand protection

Use safety gloves of following materials: NBR (nitrile) / neopren / viton (permeationslevel 5 - 6), Cat. II according to norm EN 374/EN 388.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Gloves must be periodically inspected and changed in case of wear, perforations or contaminations.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Oil-resistant and hardly inflammable protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

- -aerosol or mist formation
- -Exceeding exposure limit values

Suitable respiratory protection apparatus: Respiratory equipment in case of nebulosity or aerosol: Use a mask with a filter type A2, A2/P2 or ABEK.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: clear

Odour: characteristic

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

No information available.

No information available.

boiling range:

Flammability:

Lower explosion limits:

Upper explosion limits:

No information available.

No information available.

No information available.

Flash point:

240 °C

Auto-ignition temperature:

Decomposition temperature:

PH-Value:

No information available.

No information available.

No information available.

Viscosity / kinematic: 67,75 mm²/s DIN EN ISO 3104

(at 40 °C)



according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 7 of 14

Water solubility: No information available.

Solubility in other solvents

No information available.

Partition coefficient n-octanol/water: No information available. Vapour pressure: No information available.

(at 20 °C)

Vapour pressure: No information available.

(at 50 °C)

Density (at 15 °C): 0,878 g/cm3 DIN 51757

No information available Bulk density: Relative vapour density: No information available. Particle characteristics: No information available.

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

none

Sustaining combustion: No data available

Self-ignition temperature

Solid: No information available. Gas: No information available.

Oxidizing properties

none

Other safety characteristics

Evaporation rate: No information available. Solvent separation test: No information available. Solvent content: No information available No information available. Solid content: No information available. Sublimation point: No information available. Softening point: Pour point: -33 °C Viscosity / dynamic: No information available.

Flow time: No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

Refer to chapter 10.5.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 8 of 14

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
64742-55-8	Distillates (petroleum),	hydrotreated	l light paraffini	c; Baseoil - unspe	cified				
	oral	LD50 mg/kg	> 5000	Rat	ECHA Dossier	OECD Guideline 401			
	dermal	LD50 mg/kg	> 2000	Rabbit	ECHA Dossier	OECD Guideline 402			
	inhalation (4 h) dust/mist	LC50 mg/l	> 5,53	Rat	ECHA Dossier	OECD Guideline 403			
128-39-2	2,6-di-tert-butylphenol								
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier	OECD 401			
	dermal	LD50 mg/kg	>2000	Rat	ECHA Dossier				
80-62-6	methyl methacrylate; m	ethyl 2-meth	ıylprop-2-enoa	ate; methyl 2-methy	ylpropenoate*				
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier	WoE			
	dermal	LD50 mg/kg	> 5000	Rabbit	ECHA Dossier	OECD Guideline 402			
	inhalation (4 h) dust/mist	LC50	29,8 mg/l	Rat	ECHA Dossier				

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified:

In vitro mutagenicity/genotoxicity:

Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay) with modifications

Results: negative. / positive.

Method: OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

Results: negative.

Method: OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Results: negative. / positive.

Literature information: REACH Dossier In vivo mutagenicity/genotoxicity

Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Results: negative.; Literature information: REACH Dossier

Reproductive toxicity

Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

Exposure time: 28d; Species: Rat

Results: NOAEL = > 2000 mg/kg(bw)/day; Literature information: REACH Dossier

Developmental toxicity/teratogenicity:





according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 9 of 14

Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study)

Exposure time: 28d; Species: Rat

Results: NOAEL = > 2000 mg/kg(bw)/day; Literature information: REACH Dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified:

Subacute inhalative toxicity: Method: -; Exposure time: 28d; Species: Rat; Results: NOAEL > 980 mg/m3; Literature information: J Appl Toxicol, Vol 11(4), pp 297-302; Subacute dermal toxicity: Method: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study); Exposure time: 28d; Species: Rabbit; Results: NOAEL 1000 mg/kg(bw)/day; Literature information: REACH Dossier; Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents); Species: Rat; Results:

NOAEL = 125 mg/kg; Literature information: REACH Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance (> 0,1 %) that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

Frequently or prolonged contact with skin may cause dermal irritation.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name									
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified									
	Acute fish toxicity	LC50 100 mg/l	LL50 >	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier	OECD Guideline 203			
	Acute crustacea toxicity	EC50 >10000 mg	EL50 g/l	48 h	Daphnia magna (Big water flea)	ECHA Dossier	OECD Guideline 202			
	Algae toxicity	NOEC 100 mg/l	NOEL >	3 d	Pseudokirchneriella subcapitata	ECHA Dossier				
	Crustacea toxicity	NOEC 10 mg/l	NOEL >		Daphnia magna (Big water flea)	ECHA Dossier	OECD Guideline 211			
128-39-2	2,6-di-tert-butylphenol									
	Acute fish toxicity	LC50	1,4 mg/l	96 h	Pimephales promelas	ECHA Dossier				
	Acute algae toxicity	ErC50	1,4 mg/l	72 h	Pseudokirchnerella subcapitata	ECHA Dossier				
	Acute crustacea toxicity	EC50 mg/l	0,45	48 h	daphnia magna	ECHA Dossier				
	Fish toxicity	NOEC mg/l	0,053	42 d	Oryzias latipes	ECHA Dossier				
	Crustacea toxicity	NOEC mg/l	0,023	21 d	Daphnia magna	ECHA Dossier				
80-62-6	methyl methacrylate; met	hyl 2-methylp	orop-2-enoat	te; methy	/l 2-methylpropenoate*					
	Acute fish toxicity	LC50	>79 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier	EPA OTS 797.1400			



according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 10 of 14

Acute algae toxicity	ErC50 mg/l	>110	. —	Pseudokirchnerella subcapitata	ECHA Dossier	OECD Guideline 201
Acute crustacea toxicity	EC50	69 mg/l	48 h	Daphnia magna	ECHA Dossier	EPA OTS 797.1300
Fish toxicity	NOEC	9,4 mg/l	35 d	Brachydanio rerio	ECHA Dossier	
Crustacea toxicity	NOEC	37 mg/l	21 d	Daphnia magna	ECHA Dossier	OECD Guideline 211
Acute bacteria toxicity	EC50	100 mg/l		activated sludge	ECHA Dossier	OECD 301C

12.2. Persistence and degradability

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

IIICOII	anical Separation.							
CAS No	Chemical name							
	Method	Value	d	Source				
	Evaluation			-				
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil	- unspecified						
	OECD Guideline 301 F	31%	28	ECHA Dossier				
	Not easily bio-degradable (according to OECD-criteria).							
128-39-2	2,6-di-tert-butylphenol							
	OECD 301C / ISO 9408 / EEC 92/69 annex V, C.4-F	4,5	28	ECHA Dossier				
	Not easily bio-degradable (according to OECD-criteria).							
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*							
	OECD 301C / ISO 9408 / EWG 92/69 Anhang V,	94%	14	ECHA Dossier				
	C.4-F							
	Readily biodegradable (according to OECD criteria).							

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	> 3,5
128-39-2	2,6-di-tert-butylphenol	4,5
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*	1,32

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.7. Other adverse effects

No information available.

Further information

Ozone depletion potential (ODP): No information available.

SECTION 13: Disposal considerations



according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 11 of 14

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 9006

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es):914.4. Packing group:-Hazard label:-Classification code:M12

Marine transport (IMDG)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Informations for safe handling see chapter 7.

Informations for personal protective equipment see chapter 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75





according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 12 of 14

Directive 2010/75/EU on industrial

emissions:

No information available.

Directive 2004/42/EC on VOC in

paints and varnishes:

No information available.

Information according to Directive

2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No (mixture): 3 Observe in addition any national regulations!

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Regulation (EC) No 649/2012 of the European Parliament and of the Council concerning the export and import of dangerous chemicals: not relevant

15.2 Chemical Safety Assessment not applicable.

SECTION 16: Other information

Changes

Rev.: 1,0 - 28.11.2016 Rev.: 2,0 - 27.11.2017 Rev.: 3,0 - 27.11.2018

Rev.: 4,0 - 29.11.2019, Changes in chapter: 1.2, 8.1, 10.3, 15.1, 16

Rev.: 5,0 - 19.11.2020, Changes in chapter: 15.1, 16

Rev.: 6,0 - 30.11.2021, Changes in chapter: 3.2, 6.1, 6.3, 8.1, 8.2, 11.1, 11.2, 12.1, 12.2, 12.3, 12.6, 12.7,

15.1, 16

Rev.: 7.0 - 21.11.2022, Changes in chapter: 2.3, 3.2, 8.1, 11.1, 12.1, 12.2, 12.3, 12.5, 12.6, 15.1 16

Rev.: 8.0 - 13.11.2023, Changes in chapter: 8.1, 9.1, 11.2, 12.1, 12.7, 14, 16



according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 13 of 14

Abbreviations and acronyms

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

ECHA: European Chemicals Agency EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect concentration

NLP: No-Longer Polymers N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern TRGS: Technische Regeln für Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds WGK: Water Hazard Class (Germany)

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.



according to Regulation (EC) No 1907/2006

SRS Wiolan HVX 68

Revision date: 13.11.2023 Page 14 of 14

H335 May cause respiratory irritation. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.
Environmental hazards: Calculation method.
Physical hazards: On basis of test data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)