

SRS ViVA 1 special V eco



Special High Performance Low Friction Engine Oil

May 2024

Characteristics

SRS ViVA 1 special V eco is a high performance low friction 0W-20 engine oil based on modern synthetic technology.

Excellent low temperature flow characteristics protect optimal the engine during the cold starting. Extreme loads and high temperatures are safely handled under all operating conditions. It ensures extremely high wear protection and significantly reduced friction losses and is extremely shear-resistant.

SRS ViVA 1 special V eco contributes through its high fuel economy and reduction of emissions to protect the environment.

Application

SRS ViVA 1 special V eco is a top quality for the latest Volvo VEA passenger car engines and is especially approved according to the Volvo specification VCC RBS0-2 AE.

Specification

- SAE Grade 0W-20
- ACEA C5
- API SP

Approvals

- Volvo VCC RBS0-2AE

SRS ViVA 1 special V eco is a product of the H&R ChemPharm GmbH.

| Typical Data | Test Method | SRS ViVA 1 special V eco |
|-------------------------------|------------------|--------------------------|
| SAE Grade | SAE J 300 | 0W-20 |
| Density at 15°C | DIN EN ISO 12185 | 0.845 |
| Dyn. Viscosity at -35°C (CCS) | ASTM D 5293 | 5,680 |
| Kin. Viscosity at 40°C | DIN EN ISO 3104 | 44.7 |
| Kin. Viscosity at 100°C | DIN EN ISO 3104 | 8.79 |
| Viscosity Index (VI) | DIN ISO 2909 | 181 |
| Flash Point COC | DIN EN ISO 2592 | 232 |
| Pour Point | DIN EN ISO 3016 | -48 |

The above values may vary within the commercial limits.

Made in Germany

