SRS ViVA 1 special V eco

Special High Performance Low Friction Engine Oil

SCHMIERSTOFF VERTRIEB GMBH

September 2026

Characteristics

SRS ViVA 1 special V eco is a high performance low friction 0W-20 engine oil based on modern synthetic technology.

Excellent low temperature flow characteristics protect optimal the engine during the cold starting. Extreme loads and high temperatures are safely handled under all operating conditions. It ensures extremely high wear protection and significantly reduced friction losses and is extremely shear-resistant.
SRS ViVA 1 special V eco contributes through its high fuel economy and reduction of emissions to protect the environment.

Application

SRS ViVA 1 special V eco is a top quality for the latest Volvo VEA passenger car engines and is especially approved according to the Volvo specification VCC RBS0-2 AE.

Specification

- SAE Grade 0W-20
- ACEA C5
- API SP

Approvals / Recommendations

- Volvo VCC RBS0-2AE

SRS ViVA 1 special V eco is a product of the H&R ChemPharm GmbH.

Typical Data		Test Method	SRS ViVA 1 special V eco
SAE Grade		SAE J 300	0W-20
Density at 15°C	g/cm³	DIN EN ISO 12185	0.845
Dyn. Viscosity at -35°C (CCS)	mPa s	ASTM D 5293	5,680
Kin. Viscosity at 40°C	mm²/s	DIN EN ISO 3104	44.7
Kin. Viscosity at 100°C	mm²/s	DIN EN ISO 3104	8.79
Viscosity Index (VI)		DIN ISO 2909	181
Flash Point COC	°C	DIN EN ISO 2592	232
Pour Point	°C	ASTM D 5950	-48

The above values may vary within the commercial limits.

Made in Germany

EELQMS

SRS Schmierstoff Vertrieb GmbH • Neuenkirchener Straße 8 • 48499 Salzbergen
Phone + 49 (0) 5976 945-0 • Fax +49 (0) 5976 945-621 • Internet: http://www.srs-oil.com • E-mail: info@srs-oil.de