

SRS ViVA 1 SLV ultra



Premium-High-Performance-Longlife-Engine-Oil

November 2025

Characteristics

SRS ViVA 1 SLV ultra is a premium-high-performance-longlife engine oil for the latest passenger car engines, based on newest synthetic technology and a specially tailored innovative additive package. It meets the stricter requirements of the new API (American Petroleum Institute) SQ specification regarding fuel efficiency, protection against low-speed pre-ignition (LSPI), improved cleaning power, and longer service life. SRS ViVA 1 SLV ultra ensures very high wear protection and significantly reduced friction losses, contributing to higher fuel efficiency. Excellent cold start performance ensures optimum lubrication safety in the cold start phase. Extreme loads and high temperatures are safely handled under all operating conditions. By meeting the highest fuel economy requirements, SRS ViVA 1 SLV ultra not only helps protect the environment by reducing emissions (CO2 reduction), but also extends the service life of OPF/GPF particulate filters by limiting the sulfated ash content in accordance with API SQ. Minimal evaporation reduces oil consumption and allows for the longest oil change intervals in accordance with the respective manufacturer's specifications. The use of SRS ViVA 1 SLV ultra prevents premature fuel ignition (LSPI) and associated engine damage.

Application

SRS ViVA 1 SLV ultra has been especially developed for use in the latest engines such as Diesel engines with EURO 6 (DPF) and SCR exhaust aftertreatment, gasoline engines with exhaust turbocharging and OPF / GPF, and for the more stringent requirements of modern hybrid vehicles.

SRS ViVA 1 SLV ultra can be used in engines of the Volkswagen group with extended drain intervals (WIV). Oil change intervals up to 50.000 km or 2 years are possible. SRS ViVA 1 SLV ultra can be used in almost all long-life VW engines and is backwards compatible. The operating manuals of the OEM's must be observed.

In addition to the MB specification 229.52, SRS ViVA 1 SLV ultra also fulfills the MB specifications 229.51 and 229.31 and can therefore also be used in Daimler engines that require these specifications.

Specifications

- SAE Grade 5W-30
- ACEA C3
- API SQ

Approvals

- VW Norm 504 00 and 507 00
- MB-Approval 229.52
- BMW Longlife-04
- Porsche C30

Recommendations

- Opel / Vauxhall OV 0401547-G30
- Opel / Vauxhall OV 0401547-D30

SRS ViVA 1 SLV ultra is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS ViVA 1 SLV ultra
SAE Grade	SAE J 300	5W-30
Density at 15°C	DIN EN ISO 12185	0.852
Dyn. Viscosity at -30°C (CCS)	ASTM D 5293	5,850
Kin. Viscosity at 40°C	DIN EN ISO 3104	68.8
Kin. Viscosity at 100°C	DIN EN ISO 3104	11.9
Viscosity Index (VI)	DIN ISO 2909	170
Flash Point COC	DIN EN ISO 2592	238
Pour Point	ASTM D 5950	-42

The above values may vary within the commercial limits.

Made in Germany

