

SRS Violin ATF III MV



Multifunctional Automatic Transmission Oil

March 2025

Characteristics

SRS Violin ATF III MV is an automatic transmission fluid made from selected base oils and a high performance additive package based on modern synthetic technology. SRS Violin ATF III MV can be used in modern passenger cars and commercial vehicles automatic transmissions and steering systems. It has very good wear-, corrosion- and oxidation protection and a high friction stability.

Application

SRS Violin ATF III MV is a multifunctional automatic transmission fluid which meets the requirements of many European, American and Asian manufacturers. It is suitable for use in automatic transmissions that are equipped with or without the slip locking clutch. SRS Violin ATF III MV can also be used in automatic transmissions requiring the MB-Specification MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11, 236.12, 236.14, 236.15, 236.41, 236.81 or 236.91. Because of the backward compatibility to older models, SRS Violin ATF III MV can reduce product storage. It can also be used in vehicles in which the MAN specification MAN Type 339 V1 / Z1 required.

SRS Violin ATF III MV is not suitable for use in DCT / DSG or CVT transmissions.

Specifications

- JASO 1-A

Approvals

- DTFR 13C170
- ZF Approval Number ZF002061
- ZF TE-ML 04D, 14B, 20B, 25B
- Voith H55.6336.XX
- Voith-DIWA H59.633648
- MAN 339 Type V2 / Z2 and Z11

Recommendations

- Aisin Warner JWS 3309
- Allison TES-295 / -389, Allison C-4
- BMW 7045E, 8072B, LA 2634, LT 71141, M 1375.4
- Chrysler ATF +3, +4, MOPAR ASRC
- Ford Mercon V
- GM DEXRON IIIH, IIIG, IID
- Honda ATF Z-1
- Hyundai / KIA SP-II, SP-III, JWS 3314, JWS 3317
- Idemitsu K17 (JATCO)
- Isuzu NPR ECO MAX, NPR HD, NPR XD, NQR and NRR-SCS
- KIA Red-1 / Red-1K
- Mazda ATF-M III, ATF-MV
- MAN 339 type L1 / V1 / Z1
- Mitsubishi Diaqueen ATF J3, SP-II, SP-III
- Nissan 402, Nissan Matic-D, J, K
- PSA AL-4
- Renault DP-0
- Saab 3309
- Subaru ATF, ATF-HP
- Suzuki 3314, 3317
- Toyota T, T-II, T-III, T-IV
- Volvo 97340, 97341
- Volvo 4 speed (P/N 1161621), (P/N 1161540)
- VW G 052 162, G 052 990, G 055 025
- VW G 055 005, G 055 162, G 052 540
- ZF TE-ML 03D, 05L, 09, 11A, 11B, 14A, 16L, 16R, 17C, 21L

SRS Violin ATF III MV is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Violin ATF III MV
Colour	DIN ISO 2049	red
Density at 15°C	DIN 51 757	0.851
Dyn. Viscosity at – 40°C (CCS)	DIN 51 398	<20,000
Kin. Viscosity at 40°C	DIN EN ISO 3104	36.0
Kin. Viscosity at 100°C	DIN EN ISO 3104	7.49
Viscosity Index (VI)	DIN ISO 2909	182
Flash Point COC	DIN ISO 2592	210
Pour Point	DIN ISO 3016	- 54

The above values may vary within the commercial limits.

Made in Germany