

SRS ViVA 1 topsynth plus FE



High Performance Low Friction Engine Oil

January 2025

Characteristics

SRS ViVA 1 topsynth plus FE is a high performance low friction engine oil of the viscosity grade SAE 5W-30. Base oils based on the latest synthesis technology and innovative additives ensure compliance with of today's practical requirements. Excellent cold-start behaviour ensures optimum lubrication reliability in the cold-running phase. Extreme loads and high temperatures are safely handled under all operating conditions. SRS ViVA 1 topsynth plus FE ensures optimum engine cleanliness, reduces frictional losses in the engine and protects against wear, resulting in a longer engine life.

SRS ViVA 1 topsynth plus FE contributes to the protection of the environment through its high fuel saving and the consequent reduction in emissions.

Application

SRS ViVA 1 topsynth plus FE is a top quality for passenger car gasoline and diesel engines with and without turbocharging and direct injection engines of the latest generation. The highest demands currently made on automobile engine oils are satisfied with more than enough reserve even after extended oil change intervals.

Specifications

- SAE Grade 5W-30
- ACEA A3/B4
- API SP

Recommendations

- MB 229.5
- VW 502 00 and 505 00
- BMW Longlife-01
- Renault RN 0700 / 0710

SRS ViVA 1 topsynth plus FE is a product of the H&R ChemPharm GmbH.

Typical data	Test method	SRS ViVA 1 topsynth plus FE
SAE Grade	SAE J 300	5W-30
Density at 15°C g/cm ³	DIN 51 757	0.857
Dyn. Viscosity at -35°C mPa s	ASTM D 5293	17,600
Kin. Viscosity at 40°C mm ² /s	DIN EN ISO 3104	73.1
Kin. Viscosity at 100°C mm ² /s	DIN EN ISO 3104	12.1
Viscosity Index (VI)	DIN ISO 2909	162
Flash point COC °C	DIN ISO 2592	240
Pour point °C	DIN ISO 3016	-42

The above values may vary within the commercial limits.

Made in Germany

