



according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SRS Getriebefluid MGS 75W-90

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

gear oil

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	SRS Schmierstoff Vertrieb GmbH
Street:	Neuenkirchener Straße 8
Place:	D-48497 Salzbergen
Telephone:	05976 - 945-0
Responsible Department:	Abt. Produktsicherheit: info.reach@srs-oil.de
1.4. Emergency telephone	Gift-Informationszentrum Nord (Göttingen) - Telefon 0551-19240

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

H412

Regulation (EC) No 1272/2008

Hazard statements

Harmful to aquatic life with long lasting effects.

Precautionary statements

P273	Avoid release to the environment.
P501	Dispose of contents/container to local/regional/national/international regulations.
Special labelling	of certain mixtures
EUH208	Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2
	-methylpropenoate. May produce an allergic reaction.

2.3. Other hazards

This mixture contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH. For information or further instructions, see also section 11 or 12.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mineral oil + Additive

Relevant ingredients

CAS No	o Chemical name					
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No 1	272/2008)				



according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

Page 2 of 17

64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			
	265-159-2	649-469-00-9	01-2119480132-48	
	Asp. Tox. 1; H304	•		
157707-86- 3	Dec-1-ene, trimers, hydrogenated			10 - < 12 %
	500-183-1		01-2119486452-34	
	Asp. Tox. 1; H304			
	Mineral Oil* (64742-54-7, 64742-65-0, 64742-56-9)			7 - < 10 %
	Asp. Tox. 1; H304			
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**			0.2 - < 0.3 %
	201-297-1	607-035-00-6		
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens	1335		
68955-53-3	Amines, C12-14-tert-alkyl			< 0.1 %
	701-175-2		01-2119456798-18	
	Acute Tox. 2, Acute Tox. 3, Acute ⁻ 1, Aquatic Chronic 1; H330 H311 H	Aquatic Acute		
1213789-63 -9	(Z)-octadec-9-enylamine, C16-18-(-alkylamines	even numbered, saturated and unsa	turated)	< 0.1 %
	627-034-4		01-2119473797-19	
	Acute Tox. 4, Skin Corr. 1B, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H335 H373 H304 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc	Limits, M-factors and ATE	
64742-56-9	265-159-2	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	65 - < 70 %
	inhalation: LC LD50 = >5000	:50 = >5,53 mg/l (dusts or mists); dermal: LD50 = >5000 mg/kg; oral: mg/kg	
157707-86- 3	500-183-1	Dec-1-ene, trimers, hydrogenated	10 - < 12 %
	inhalation: LC LD50 = >5000	50 = >5,2 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: mg/kg	
80-62-6	201-297-1	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**	0.2 - < 0.3 %
	inhalation: LC LD50 = 8400 i	:50 = 29,8 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: mg/kg	
68955-53-3	701-175-2	Amines, C12-14-tert-alkyl	< 0.1 %
		:50 = 1,19 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); = 251 mg/kg; oral: LD50 = 552 mg/kg Skin Sens. 1A; H317: >= 5 - 100	
1213789-63 -9	627-034-4	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	< 0.1 %
	M=10	= > 2000 mg/kg; oral: LD50 = 1200 mg/kg Aquatic Acute 1; H400:	
	Aquatic Chron	ic 1; H410: M=10	

Further Information

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide



according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

Page 3 of 17

extraction refractive index method" Institute of Petroleum, London).

*The mineral oil can be described by one or more EINECS numbers. 265-157-1, 265-169-7, 265-159-2, (REACH-no.: 01-2119484627-25, 01-2119471299-27, 01-2119480132-48)

**Substance for which a community occupational exposure limit value applies in the European Union.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

If swallowed or in the event of vomiting, risk of entering the lungs.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Sand. Foam. Carbon dioxide (CO2). Extinguishing powder. In case of major fire and large quantities: Water spray jet. Water mist.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO2) Sulphur dioxide (SO2) Nitrogen oxides (NOx)

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures



according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

Page 4 of 17

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ventilate affected area.

Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Wear personal protection equipment (refer to section 8).

For emergency responders

No special measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil. If required, notify relevant authorities according to all applicable regulations.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

No information available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wear suitable protective clothing. (See section 8.) Avoid formation of oil dust.

Advice on protection against fire and explosion

Usual measures for fire prevention. Keep away from sources of ignition - No smoking. Fire class ${\sf B}$

Advice on general occupational hygiene

Clean skin thoroughly after working. Do not put any product-impregnated cleaning rags into your trouser pockets. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

Further information on handling

Do not breathe vapour/aerosol. Avoid contact with eyes and skin. General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

Hints on joint storage

Do not store together with: Gas. Explosives. Oxidizing substances. Radioactive substances. Infectious substances

Further information on storage conditions

Temperature control required. Protect from light. Keep container tightly closed. Do not allow contact with air.

7.3. Specific end use(s)

See section 1.



according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

Page 5 of 17

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m³	fib/cm³	Category	Origin
80-62-6	Methyl methacrylate	50	-		TWA (8 h)	
		100	-		STEL (15 min)	

DNEL/DMEL values

CAS No	Name of agent						
DNEL type		Exposure route	Effect	Value			
64742-56-9	5-9 Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified						
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³			
Worker DNEL,	long-term	inhalation	local	5,58 mg/m³			
Worker DNEL,	long-term	dermal	systemic	0,97 mg/kg bw/day			
Consumer DNI	EL, long-term	oral	systemic	0,74 mg/kg bw/day			
Consumer DN	EL, long-term	inhalation	local	1,19 mg/m³			
68955-53-3	Amines, C12-14-tert-alkyl						
Consumer DN	EL, long-term	inhalation	systemic	2,5 mg/m³			
Consumer DN	EL, long-term	inhalation	local	1,2 mg/m³			
Worker DNEL,	long-term	inhalation	systemic	12,5 mg/m³			
Worker DNEL,	long-term	inhalation	local	12,1 mg/m³			
, 1213789-6 3-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, satura	ted and unsaturated)-a	lkylamines				
Worker DNEL,	long-term	inhalation	systemic	0,38 mg/m³			
Worker DNEL,	long-term	inhalation	local	1 mg/m³			
Worker DNEL, acute		inhalation	local	1 mg/m³			
Consumer DN	EL, long-term	inhalation	systemic	0,035 mg/m³			
Consumer DN	EL, long-term	oral	systemic	0,04 mg/kg bw/day			

PNEC values

CAS No	Name of agent				
Environmental	compartment	Value			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified				
Secondary poisoning 9,33 mg/kg					
68955-53-3 Amines, C12-14-tert-alkyl					
Freshwater 0,001 mg/l					
Freshwater (intermittent releases) 0,004 mg					
Marine water 0 mg					
Freshwater sediment 2,14 mg/kg					
Marine sediment 0,214 mg					



Revision date: 04.03.2025

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Page 6 of 17

Secondary po	4,71 mg/kg			
Micro-organis	sms in sewage treatment plants (STP)	0,635 mg/l		
Soil		0.428 mg/kg		
1213789-6 (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines 3-9				
Freshwater	·	0,00026 mg/l		
Freshwater (i	0,0016 mg/l			
Marine water		0,000026 mg/l		
Freshwater s	ediment	3,76 mg/kg		
Marine sedim	0,376 mg/kg			
Micro-organis	0,55 mg/l			
Soil	10 mg/kg			

Additional advice on limit values

Air limit values: Possibility of exposure to Aerosol (Mineral oil) Limit value (TLV-TWA) = 5 mg/ m3 - Source: ACGIH Limit value (TLV-STEL) = 10 mg/ m3 - Source: ACGIH

STEL: short-term exposure limits TLV: Threshold Limiting Value TWA: time weighted average ACGIH:American Conference of Governmental Industrial Hygienists

8.2. Exposure controls



Appropriate engineering controls Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety goggles with side protection. In case of increased risk add protective face shield. EN 166

Hand protection

Use safety gloves of following materials: NBR (nitrile) / neopren / viton (permeationslevel 5 - 6), Cat. II according to norm EN 374/EN 388.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Gloves must be periodically inspected and changed in case of wear, perforations or contaminations. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Oil-resistant and hardly inflammable protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection necessary at: -aerosol or mist formation -Exceeding exposure limit values

Suitable respiratory protection apparatus: Respiratory equipment in case of nebulosity or aerosol: Use a





according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

Physical state:

mask with a filter type A2, A2/P2 or ABEK. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

liquid

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Filysical state.	liquiu		
Colour:	clear		
Odour:	characteristic		
			Test method
Melting point/freezing point:		No information available.	
Boiling point or initial boiling point and		No information available.	
boiling range:			
Flammability:		No information available.	
Lower explosion limits:		No information available.	
Upper explosion limits:		No information available.	
Flash point:		210 °C	DIN ISO 2592
Auto-ignition temperature:		No information available.	
Decomposition temperature:		No information available.	
pH-Value:		No information available.	
Viscosity / kinematic: (at 40 °C)		75,8 mm²/s	DIN EN ISO 3104
Water solubility:		No information available.	
Solubility in other solvents			
No information available.			
Partition coefficient n-octanol/water:		No information available.	
Vapour pressure:		No information available.	
(at 20 °C)			
Vapour pressure:		No information available.	
(at 50 °C)		<i>i</i>	
Density (at 15 °C):		0,877 g/cm ³	DIN 51757
Bulk density:		No information available.	
Relative vapour density:		No information available.	
Particle characteristics:		No information available.	
 Other information			
Information with regard to physical haza –	ard classes		
Explosive properties			
none			
Sustaining combustion:		No data available	
Self-ignition temperature			
Solid: Gas:		No information available. No information available.	
Oxidizing properties			
none			
Other safety characteristics			
Evaporation rate:		No information available.	
Solvent separation test:		No information available.	
Solvent content:		No information available.	

Page 7 of 17



according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

Page 8 of 17

Solid content: Sublimation point:	No information available. No information available. No information available.
Softening point: Pour point:	-48 °C ASTM D 5985 No information available.
Viscosity / dynamic: Flow time:	No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reactions known. Refer to chapter 10.5.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-56-9	Distillates (petroleum), solvent-dew	axed light pa	raffinic; Baseoil - ur	nspecified	
	oral	LD50 mg/kg	>5000	Rat.	ECHA Dossier	
	dermal	LD50 mg/kg	>5000	Rabbit.	ECHA Dossier	
	inhalation (4 h) dust/mist	LC50 mg/l	>5,53	Rat.	ECHA Dossier	
157707-86- 3	Dec-1-ene, trimers, h	ydrogenated				
	oral	LD50 mg/kg	>5000	Rat.	ECHA Dossier	
	dermal	LD50 mg/kg	>2000	Rat.	ECHA Dossier	



according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

Page 9 of 17

						0		
	inhalation (4 h) dust/mist	LC50 mg/l	>5,2	Rat.	ECHA Dossier	OECD 403		
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**							
	oral	LD50 mg/kg	8400	Rat				
	dermal	LD50 mg/kg	> 5000	Rabbit	ECHA Dossier			
	inhalation (4 h) dust/mist	LC50 mg/l	29,8	Rat	ECHA Dossier			
68955-53-3	Amines, C12-14-tert-alkyl							
	oral	LD50 mg/kg	552	Rat	ECHA Dossier	OECD 401		
	dermal	LD50 mg/kg	251	Rat	ECHA Dossier	OECD 402		
	inhalation (4 h) vapour	LC50 mg/l	1,19	Rat	ECHA Dossier	OECD 403		
	inhalation dust/mist	ATE mg/l	0,05					
1213789-6 3-9	(Z)-octadec-9-enylamir	e, C16-18-(e	even number	ed, saturated and	unsaturated)-alkylamines			
	oral	LD50 mg/kg	1200	Rat	REACH Dossier	OECD Guideline 401		
	dermal	LD50 mg/kg	> 2000	Rat	REACH Dossier	OECD Guideline 402		

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate. May produce an allergic reaction.

Skin sensitisation:

Amines, C12-14-tert-alkyl (Conc.= 5%)

Test results: not sensitizing. Method: Buehler Method OECD 406, Species: Guinea-pig. Literature information: Manufacturer

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met. Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified: In vitro mutagenicity/genotoxicity:

Method: OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test), OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test), OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative Literature information: REACH Dossier; Chronic dermal toxicity: Exposure time: ~546 d; Species: Mouse.; Method: OECD Guideline 451; Result: Carcinogenicity = negative Literature information: REACH Dossier; Reproductive toxicity: Exposure route: oral. Species: Rat.; Method: OECD Guideline 421;Result: NOAEL >1000 mg/kg; Literature information: REACH Dossier; Developmental toxicity/teratogenicity: Exposure route: dermal. Species: Rat.; Method: OECD Guideline 414; Result: NOAEL >2000 mg/kg; Literature information: REACH Dossier



according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

Page 10 of 17

Dec-1-ene, trimers, hydrogenated:

In vitro mutagenicity/genotoxicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative Literature information: REACH Dossier; Reproductive toxicity: Species: Rat; Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test); Result: NOAEL > 1000 mg/kg; Literature information: REACH Dossier

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate:

In-vitro mutagenicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative Literature information: REACH Dossier; Carcinogenicity: negative Method: OECD Guideline 451 (Carcinogenicity Studies, 6h/d); Species: Rat,oral.; Exposure duration: 2 years; Result: NOAEC >= 2000 ppm; Literature information: REACH Dossier; Reproductive toxicity: Method: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study); Species: Rat; Result: NOAEL = 400 mg/kg; Literature information: REACH Dossier; 1. Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Species: Rabit.

Exposure duration: 28d; Result: NOAEL = 450 mg/kg

2. Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Species: Rat; Result: NOAEC >= 8,3 mg/l; Literature information: REACH Dossier

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines: In-vitro mutagenicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay) (reliability scoring based on 1997 guideline), OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test): OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test); Results: negative; Literature information: REACH Dossier

Developmental toxicity/teratogenicity: Method: 40 CFR Part 798.4700; Species: Rat; Result: NOAEL > 80 mg/kg; Species: Rabbit ; Result: NOAEL > 30 mg/kg; Literature information: REACH Dossier

Amines, C12-14-tert-alkyl: In-vitro mutagenicity: Method: -OECD Guideline 471 (Bacterial Reverse Mutation Assay) -OECD Guideline 476 (In Vitro Mammalian Cell Gene Mutation Test) Result: negative Literature information: REACH Dossier

In vivo mutagenicity/genotoxicity: Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) Species: Mouse. Results: negative Literature information: REACH Dossier

Reproductive toxicity: Species: Rat. Method: OECD Guideline 415 Result: NOAEL(F1) >= 511 < 511 ppm (Symptoms/ delayed effects: body weight) Developmental toxicity/teratogenicity: Exposure time: 21d, dermal. Species: Rat. Method: OECD Guideline 414 Result: NOAEL (Maternal toxicity) = 5 mg/kg bw/day; NOAEL (fetus) = 45 mg/kg bw/day Literature information: REACH Dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

Page 11 of 17

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified: Subchronic oral toxicity: Exposure time: 90d; Species: Sprague-Dawley Rat.; Method: OECD Guideline 408; Result: LOAEL = 125 mg/kg; Literature information: REACH Dossier; Subacute inhalative toxicity : Exposure time: 28d; Species: Spraque-Dawley Rat.; Result: NOAEC > 980 mg/m3; Literature information: REACH Dossier; Subacute dermal toxicity: Exposure time: 28d; Species: Rabbit; Method: OECD Guideline 410; Result: NOAEL 1000 mg/kg; Literature information: REACH Dossier Dec-1-ene, trimers, hydrogenated: Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Species: Rat; Results: NOAEL 1000 mg/kg; Literature information: REACH Dossier methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate: Chronic oral toxicity: Method: -: Species: Rat:Exposure duration: 2 years; Results: NOAEL = 2000 ppm. Literature information: REACH Dossier; 1. Chronic inhalation toxicity: Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies, 6h/d); Species: Rat; Exposure duration: approx. 2 years; Results: LOAEC = 250 ppm. 2. Chronic inhalation toxicity: Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies, 6h/d); Species: Rat; Exposure duration: approx. 2 years; Results: NOAEC = 1,64 m/l; Literature information: REACH Dossier (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines: Subacute oral toxicity: Method: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents) Species: Rat: Exposure duration: 28 d Results: NOAEL = 3,25 mg/kg; Literature information: REACH Dossier Amines, C12-14-tert-alkyl: Subchronic inhalative toxicity: Method: OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day) Species: Rat Results: NOAEC = 19 mg/m3 Literature information: REACH Dossier Subacute dermal toxicity Method: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) Species: Rat Results: NOAEL = 20 mg/kg Literature information: REACH Dossier Aspiration hazard Based on available data, the classification criteria are not met. 11.2. Information on other hazards Endocrine disrupting properties This product does not contain a substance (> 0,1 %) that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria. Other information Frequently or prolonged contact with skin may cause dermal irritation. **SECTION 12: Ecological information** 12.1. Toxicity Harmful to aquatic life with long lasting effects.

CAS	No	Chemical name					
		Aquatic toxicity	Dose	[h] [d	Species	Source	Method



Page 12 of 17

according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

64742-56- 9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified								
	Acute fish toxicity	LC50 mg/l	>100	96 h	Pimephales promelas	ECHA Dossier			
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Pseudokirchnerella subcapitata	ECHA Dossier			
	Acute crustacea toxicity	EC50 mg/l	>10000	48 h	Daphnia magna	ECHA Dossier			
	Crustacea toxicity	NOEC	10 mg/l	21 d	Daphnia magna	ECHA Dossier			
157707-86 ·3	Dec-1-ene, trimers, hyd	•							
	Acute fish toxicity	LL50 mg/l	>1000	96 h	Pimephales promelas	ECHA Dossier	USEPA (1975)		
	Acute crustacea toxicity	EL50 mg/l	>1000	48 h	Daphnia magna	ECHA Dossier	OECD Guideline 202		
	Crustacea toxicity	NOEC mg/l	125	21 d	Daphnia magna	ECHA Dossier	OECD Guideline 211		
80-62-6	methyl methacrylate; m	ethyl 2-methy	lprop-2-enoat	e; meth	/I 2-methylpropenoate**				
	Acute fish toxicity	LC50 mg/l	410		Pimephales promelas	ECHA Dossier			
	Acute algae toxicity	ErC50 mg/l	>110	72 h	Pseudokirchnerella subcapitata (OECD 201)	ECHA Dossier			
	Acute crustacea toxicity	EC50 mg/l	720	48 h	Daphnia magna	ECHA Dossier			
68955-53- 3	Amines, C12-14-tert-alkyl								
	Acute fish toxicity	LC50	1,3 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier	OECD Guideline 203		
	Acute algae toxicity	ErC50 mg/l	0,44	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	OECD 201		
	Acute crustacea toxicity	EC50	4,1 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD Guideline 202		
	Fish toxicity	NOEC mg/l	0,078	96 c	Oncorhynchus mykiss	ECHA Dossier	OECD Guideline 210		
	Acute bacteria toxicity	EC50 mg/l()	63,5	0,5 h	activated sludge of a predominantly domestic sewage	ECHA Dossier	OECD Guideline 209		
1213789-6 3-9	(Z)-octadec-9-enylamin	e, C16-18-(ev	ven numbered	l, saturat	ed and unsaturated)-all	kylamines			
	Acute fish toxicity	LC50 mg/l	0,06	96 h	Pimephales promelas	REACH Dossier	EPA OPPTS 850.1085		
	Acute algae toxicity	ErC50 mg/l	0,38	72 h	Desmodesmus subspicatus	REACH Dossier	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	0,98	48 h	Daphnia magna	REACH Dossier	OECD Guideline 202		
	Crustacea toxicity	NOEC mg/l	0,013	21 d	Daphnia magna	REACH Dossier	OECD Guideline 211		



according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date	e: 04.03.2025					Page 13 of 1	
	Acute bacteria toxicity	EC50 222,5 mg/l ()	3 h	activated sludge	REACH Do	ssier OECD Guideline 209	
12.2. Persist	ence and degradability						
•	roduct is slightly soluble in anical separation.	n water. It can be large	ely elimir	nated from the wate	er by abiotic pro	cesses, e.g.	
CAS No	Chemical name						
	Method			Value	d	Source	
	Evaluation						
64742-56-9	Distillates (petroleum), sol	lvent-dewaxed light para	ffinic; Bas	seoil - unspecified			
	OECD 301B / ISO 943 C.4-C	9 / EEC 92/69 annex V,		2-4%	28	ECHA Dossier	
	Not easily bio-degradable (according to OECD-criteria).						
157707-86- 3	Dec-1-ene, trimers, hydrogenated						
	OECD 301D / EEC 92/	/69 annex V, C.4-E		2 %	28	ECHA Dossier	
	Not easily bio-degrada	ble (according to OECD-	criteria).				
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**						
	OECD 301C / ISO 940 V, C.4-F	8 / EWG 92/69 Anhang		94%	14	ECHA Dossier	
	Readily biodegradable	(according to OECD crit	eria).				
68955-53-3	Amines, C12-14-tert-alkyl						
	OECD 301D / EEC 92/	/69 annex V, C.4-E		22 %	28	ECHA Dossier	
	Not readily biodegrada	ble (according to OECD	criteria)				
1213789-6 3-9	(Z)-octadec-9-enylamine,	C16-18-(even numbered	, saturate	ed and unsaturated)-a	alkylamines		
	OECD Guideline 301 E)		66%	28	REACH Dossier	
	Readily biodegradable	(according to OECD crit	eria).				

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
157707-86-3	Dec-1-ene, trimers, hydrogenated	>6,5
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**	1,32
68955-53-3	Amines, C12-14-tert-alkyl	2,9
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated) -alkylamines	5,16

BCF

CAS No	Chemical name	BCF	Species	Source
	(Z)-octadec-9-enylamine, C16-18- (even numbered, saturated and unsaturated)-alkylamines	173		Environmental Toxico

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.



Page 14 of 17

according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.7. Other adverse effects

No information available.

Further information

Ozone depletion potential (ODP): No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste


Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

Lanu transport (ADR/RID)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 9006
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es):	9
14.4. Packing group:	-
Hazard label:	-
Classification code:	M12
Marine transport (IMDG)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
14.5. Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	No



Page 15 of 17



Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

14.6. Special precautions for user

Informations for safe handling see chapter 7. Informations for personal protective equipment see chapter 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 75	
Directive 2010/75/EU on industrial emissions:	No information available.
Directive 2004/42/EC on VOC in paints and varnishes:	No information available.
Information according to Directive 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878) The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. REACH 1907/2006 Appendix XVII, No (mixture): 3 Observe in addition any national regulations!

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). 1 - slightly hazardous to water

Water hazard class (D): Additional information

Regulation (EU) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals: not relevant

15.2 Chemical Safety Assessment not applicable.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 3,11,16.

Rev.: 1,0 - 28.04.2015 Rev.: 1,1 - 10.05.2016 Rev.: 2,0 - 02.06.2017 Rev.: 3,0 - 27.06.2018 Rev.: 4,0 - 26.06.2019 Rev.: 5,0 - 29.06.2020, Changes in chapter: 2.2, 3.2, 11.1, 15.1, 16 Rev.: 6.0 - 04.06.2021, Changes in chapter: 3.2, 6.1, 6.3, 11.2, 12.6, 12.7, 15.1, 16 Rev.: 7.0 - 14.06.2022, Changes in chapter: 2.3, 3.2, 8.2, 12.1, 12.5, 12.6, 16 Rev.: 7.1 - 01.03.2023, Changes in chapter: 2.3, 3.2, 8.1, 9.1, 11.1, 12.1, 12.2, 12.3, 12.5, 15.1, 16 Rev.: 8.0 - 06.03.2024, Changes in chapter: 8.1, 11.2, 12.1, 12.7, 14, 15.1, 16 Rev.: 9.0 - 04.03.2025, Changes in chapter: 11.1, 16




according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

Page 16 of 17

Abbreviations and acronyms Flam. Liq: Flammable liquid Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Corr: Skin corrosion Skin Irrit: Skin irritation Skin Sens: Skin sensitisation STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) CAS: Chemical Abstracts Service CLP: Classification, Labelling and Packaging of substances and mixtures d: day(s) DNEL: Derived No Effect Level IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European LIst of Notified Chemical Substances ECHA: European Chemicals Agency EWC: European Waste Catalogue IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany) h. hour LOAEL: Lowest observed adverse effect level LOAEC: Lowest observed adverse effect concentration LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NOAEL: No observed adverse effect level NOAEC: No observed adverse effect concentration NLP: No-Longer Polymers NTP: National Toxicology Program N/A: not applicable OECD: Organisation for Economic Co-operation and Development PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic PMT: Persistent, mobile and toxic REACH: Registration, Evaluation, Authorisation of Chemicals RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) SVHC: substance of very high concern TRGS: Technische Regeln für Gefahrstoffe **UN: United Nations** TSCA: Toxic Substances Control Act vPvM: very persistent and very mobile vPvB: very persistent and very bioaccumulative VOC: Volatile Organic Compounds WGK: Water Hazard Class (Germany)





according to Regulation (EC) No 1907/2006

SRS Getriebefluid MGS 75W-90

Revision date: 04.03.2025

Page 17 of 17

Key literature references and sources for data

https://echa.europa.eu/ https://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp https://cfpub.epa.gov/ecotox/search.cfm http://www.inchem.org/#/search https://pubchem.ncbi.nlm.nih.gov/ http://ccinfoweb.ccohs.ca/rtecs/search.html https://webrigoletto.uba.de/rigoletto/

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008

[CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

Highly flammable liquid and vapour.
Harmful if swallowed.
May be fatal if swallowed and enters airways.
Toxic in contact with skin.
Causes severe skin burns and eye damage.
Causes skin irritation.
May cause an allergic skin reaction.
Fatal if inhaled.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.
Very toxic to aquatic life.
Very toxic to aquatic life with long lasting effects.
Harmful to aquatic life with long lasting effects.
Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2 -methylpropenoate. May produce an allergic reaction.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)