

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

SRS Getriebefluid SBL 75W-90

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

gear oil

Uses advised against

none

1.3. Details of the supplier of the safety data sheet

Company name: SRS Schmierstoff Vertrieb GmbH
Street: Neuenkirchener Straße 8
Place: D-48497 Salzbergen
Telephone: 05976 - 945-0
Responsible Department: Abt. Produktsicherheit: info.reach@srs-oil.de
1.4. Emergency telephone number: Gift-Informationszentrum Nord (Göttingen) - Telefon 0551-19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Pictograms:****Hazard statements**

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.
P391 Collect spillage.
P501 Dispose of contents/container to local/regional/national/international regulations.

Special labelling of certain mixtures

EUH208 Contains Polysulfides, di-tert-Bu, Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched), Magnesium metaborate. May produce an allergic reaction.

2.3. Other hazards

The mixture contains the following substances fulfilling the PBT criteria according to REACH, annex XIII: O,O,O-Triphenyl phosphorothioate.

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: O,O,O-Triphenyl phosphorothioate

For information or further instructions, see also section 11 or 12.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 2 of 18

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			30 - < 35 %
	265-158-7	649-468-00-3	01-2119487077-29	
	Asp. Tox. 1; H304			
	Mineral Oil* (64742-54-7, 64742-65-0, 64742-55-8, 64742-56-9)			5 - < 7 %
	Asp. Tox. 1; H304			
68937-96-2	Polysulfides, di-tert-Bu			3 - < 5 %
	273-103-3		01-2119540515-43	
	Skin Sens. 1B, Aquatic Chronic 3; H317 H412			
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)			1 - < 3 %
	931-384-6		01-2119493620-38	
	Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H302 H319 H317 H411			
597-82-0	O,O,O-Triphenyl phosphorothioate			0.5 - < 1 %
	209-909-9		01-2119979545-21	
	Aquatic Chronic 1; H410			
13703-82-7	Magnesium metaborate			0.5 - < 1 %
	237-235-5		01-2120769073-53	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	30 - < 35 %
		inhalation: LC50 = > 5,53 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
68937-96-2	273-103-3	Polysulfides, di-tert-Bu	3 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg Skin Sens. 1B; H317: >= 46 - 100	
	931-384-6	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	1 - < 3 %
		oral: LD50 = > 2000 mg/kg Eye Irrit. 2; H319: >= 50 - 100 Skin Sens. 1; H317: >= 9,39 - 100	
597-82-0	209-909-9	O,O,O-Triphenyl phosphorothioate	0.5 - < 1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 10000 mg/kg Aquatic Chronic 1; H410: M=10	
13703-82-7	237-235-5	Magnesium metaborate	0.5 - < 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	

Further Information

*The mineral oil can be described by one or more EINECS numbers. 265-157-1, 265-169-7, 265-158-7, 265-159-2, (REACH-no.: 01-2119484627-25, 01-2119471299-27, 01-2119487077-29, 01-2119480132-48)

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 3 of 18

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London).

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

If swallowed or in the event of vomiting, risk of entering the lungs.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Sand. Foam. Carbon dioxide (CO₂). Extinguishing powder. In case of major fire and large quantities: Water spray jet. Water mist.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂) Sulphur dioxide (SO₂) Nitrogen oxides (NO_x)

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 4 of 18

General advice

- Avoid contact with skin, eyes and clothes.
- Avoid formation of oil dust.
- Ventilate affected area.
- Special danger of slipping by leaking/spilling product.

For non-emergency personnel

- Wear personal protection equipment (refer to section 8).

For emergency responders

- No special precautionary measures are necessary.

6.2. Environmental precautions

- Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil. If required, notify relevant authorities according to all applicable regulations.

6.3. Methods and material for containment and cleaning up**For containment**

- Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
- Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

- Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

- No information available.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

- Wear suitable protective clothing. (See section 8.) Avoid contact with skin, eyes and clothes.
- Avoid formation of oil dust.
- Do not breathe aerosol.

Advice on protection against fire and explosion

- Usual measures for fire prevention. Keep away from sources of ignition - No smoking.
- Fire class B

Advice on general occupational hygiene

- Clean skin thoroughly after working.
- Do not put any product-impregnated cleaning rags into your trouser pockets.
- When using do not eat, drink or smoke.

Further information on handling

- Do not breathe vapour/aerosol.
- Avoid contact with eyes and skin.
- General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

- Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

Hints on joint storage

- Do not store together with: Gas. Explosives. Oxidizing substances. Radioactive substances.. Infectious substances

Further information on storage conditions

- Temperature control required. Protect from light. Keep container tightly closed. Do not allow contact with air.

7.3. Specific end use(s)

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 5 of 18

See section 1.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****DNEL/DMEL values**

CAS No	Name of agent	Exposure route	Effect	Value
DNEL type				
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term		inhalation	local	5,58 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m ³
68937-96-2	Polysulfides, di-tert-Bu			
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)			
Worker DNEL, long-term		inhalation	systemic	4,28 mg/m ³
Worker DNEL, long-term		dermal	systemic	12,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,09 mg/m ³
Consumer DNEL, long-term		dermal	systemic	6,25 mg/kg bw/day
Consumer DNEL, acute		dermal	local	0.024 mg/cm ²
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day
597-82-0	O,O,O-Triphenyl phosphorothioate			
Worker DNEL, long-term		inhalation	systemic	1,39 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,4 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,34 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,2 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,2 mg/kg bw/day
13703-82-7	Magnesium metaborate			
Worker DNEL, long-term		inhalation	systemic	5,49 mg/m ³
Worker DNEL, long-term		dermal	systemic	7,78 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,82 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,278 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,28 mg/kg bw/day

PNEC values

CAS No	Name of agent
--------	---------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 6 of 18

Environmental compartment		Value
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	
Freshwater		0,0024 mg/l
Freshwater (intermittent releases)		0,15 mg/l
Marine water		0,00024 mg/l
Freshwater sediment		0,0129 mg/kg
Marine sediment		0,00129 mg/kg
Secondary poisoning		10 mg/kg
Micro-organisms in sewage treatment plants (STP)		24,33 mg/l
Soil		0,00117 mg/kg
597-82-0	O,O,O-Triphenyl phosphorothioate	
Freshwater		0,00017 mg/l
Marine water		0,000017 mg/l
Freshwater sediment		3,47 mg/kg
Marine sediment		0,347 mg/kg
Soil		2,46 mg/kg
13703-82-7	Magnesium metaborate	
Freshwater		0.05 mg/l
Marine water		0.05 mg/l
Freshwater sediment		1.38 mg/kg
Marine sediment		1.38 mg/kg
Secondary poisoning		1.67 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0.247 mg/kg

Additional advice on limit values

Air limit values:

Possibility of exposure to Aerosol (Mineral oil)

Limit value (TLV-TWA) = 5 mg/ m3 - Source: ACGIH

Limit value (TLV-STEEL) = 10 mg/ m3 - Source: ACGIH

STEEL: short-term exposure limits

TLV: Threshold Limiting Value

TWA: time weighted average

ACGIH: American Conference of Governmental Industrial Hygienists

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 7 of 18

Eye/face protection

Safety goggles with side protection. In case of increased risk add protective face shield. EN 166

Hand protection

Use safety gloves of following materials: NBR (nitrile) / neopren / viton (permeationslevel 5 - 6), Cat. II according to norm EN 374/EN 388.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Gloves must be periodically inspected and changed in case of wear, perforations or contaminations.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Oil-resistant and hardly inflammable protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

-aerosol or mist formation

-Exceeding exposure limit values

Suitable respiratory protection apparatus: Respiratory equipment in case of nebulosity or aerosol: Use a mask with a filter type A2, A2/P2 or ABEK.

The filter class must be suitable for the maximum contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	clear
Odour:	characteristic

Test method

Melting point/freezing point:	No information available.
Boiling point or initial boiling point and boiling range:	No information available.
Flammability:	No information available.
Lower explosion limits:	No information available.
Upper explosion limits:	No information available.
Flash point:	202 °C COC
Auto-ignition temperature:	No information available.
Decomposition temperature:	No information available.
pH-Value:	No information available.
Viscosity / kinematic: (at 40 °C)	116,5 mm ² /s
Water solubility:	No information available.
Solubility in other solvents	
No information available.	
Partition coefficient n-octanol/water:	No information available.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 8 of 18

Vapour pressure: (at 20 °C)	No information available.
Vapour pressure: (at 50 °C)	No information available.
Density (at 15 °C):	0,8781 g/cm ³
Bulk density:	No information available.
Relative vapour density:	No information available.
Particle characteristics:	No information available.

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties
none

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

No information available.

Gas:

No information available.

Oxidizing properties
none

Other safety characteristics

Evaporation rate:

No information available.

Solvent separation test:

No information available.

Solvent content:

No information available.

Solid content:

No information available.

Sublimation point:

No information available.

Softening point:

No information available.

Pour point:

-45 °C DIN EN ISO 3016

Viscosity / dynamic:

No information available.

Flow time:

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

Refer to chapter 10.5.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

No information available.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 9 of 18

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	ECHA Dossier	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	ECHA Dossier	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 > 5,53 mg/l	Rat	ECHA Dossier	OECD Guideline 403
68937-96-2	Polysulfides, di-tert-Bu				
	oral	LD50 >2000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rat	ECHA Dossier	
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)				
	oral	LD50 > 2000 mg/kg	Rat	ECHA Dossier	OECD Guideline 401
597-82-0	O,O,O-Triphenyl phosphorothioate				
	oral	LD50 > 10000 mg/kg	Rat	ECHA Dossier	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	ECHA Dossier	OECD Guideline 402
13703-82-7	Magnesium metaborate				
	oral	LD50 >2000 mg/kg	Rat	REACH Dossier	OECD Guideline 420
	dermal	LD50 >2000 mg/kg	Rat	REACH Dossier	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains Polysulfides, di-tert-Bu, Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched), Magnesium metaborate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified:

In vitro mutagenicity/genotoxicity:

Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay) with modifications

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 10 of 18

Results: negative / positive

Method: OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

Results: negative

Method: OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Results: negative / positive

Literature information: REACH Dossier

In vivo mutagenicity/genotoxicity

Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Results: negative ; Literature information: REACH Dossier

Reproductive toxicity

Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

Exposure time: 28d; Species: Rat

Results: NOAEL = > 2000 mg/kg(bw)/day; Literature information: REACH Dossier

Developmental toxicity/teratogenicity:

Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study)

Exposure time: 28d; Species: Rat

Results: NOAEL = > 2000 mg/kg(bw)/day; Literature information: REACH Dossier

Polysulfides, di-tert-Bu:

In vitro mutagenicity/genotoxicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative Literature information: REACH Dossier; Reproductive toxicity: Species: Rat (Sprague-Dawley);

Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test); Result: NOAEL = 150 mg/kg; Literature information: REACH Dossier; Developmental toxicity/teratogenicity: Species: Rat; Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Result: NOAEC >= 195 ppm; Literature information: REACH Dossier

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched):

In vitro mutagenicity/genotoxicity: Method: OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test); Result: negative Literature information: REACH Dossier; Reproductive toxicity: Species: Rat

(Wistar); Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test); Result: NOAEL = 150 mg/kg Literature information: REACH Dossier; Developmental toxicity/teratogenicity: Species: Rat (Wistar); Method: other guideline: Reproduction/developmental screening test. Result: NOAEL = 150 mg/kg; Literature information: REACH Dossier

Magnesium metaborate:

In-vitro mutagenicity:

Method:

-OECD Guideline 490 (In Vitro Mammalian Cell Gene Mutation Tests Using the Thymidine Kinase Gene)

-OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

-OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Result: negative ; Literature information: REACH Dossier

O,O,O-Triphenyl phosphorothioate:

In vitro mutagenicity/genotoxicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative Literature information: REACH Dossier; Reproductive toxicity: Species: Rat (Wistar); Method:

OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test); Result: NOAEL >250 mg/kg; Literature information: REACH Dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified:

Subacute inhalative toxicity : Method: -; Exposure time: 28d; Species: Rat; Results: NOAEL > 980 mg/m3;

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 11 of 18

Literature information: J Appl Toxicol, Vol 11(4), pp 297-302; Subacute dermal toxicity: Method: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study); Exposure time: 28d; Species: Rabbit; Results: NOAEL 1000 mg/kg(bw)/day; Literature information: REACH Dossier; Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents); Species: Rat; Results: NOAEL = 125 mg/kg; Literature information: REACH Dossier

Polysulfides, di-tert-Bu:

Subacute oral toxicity:

Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Species: Rat

Results: NOAEL = 100 mg/kg; Literature information: REACH Dossier

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched):

Subacute oral toxicity: Method: -; Species: Rat; Results: NOAEL = 150 mg/kg; Literature information: REACH Dossier

Magnesium metaborate:

Repeated dose toxicity:

Method: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Species: Rat

Exposure duration: 28 d.

Results: NOAEL = 150 mg/kg bw/day. (systemic)

Literature information: REACH Dossier

O,O,O-Triphenyl phosphorothioate:

Subacute oral toxicity Method: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents);

Species: Rat; Results: NOAEL 50 mg/kg; Literature information: REACH Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

No information available.

Other information

Frequent contact specially if dried out may cause skin and eye irritations.

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LC50 LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier	OECD Guideline 203
	Acute crustacea toxicity	EC50 EL50 >10000 mg/l	48 h	Daphnia magna (Big water flea)	ECHA Dossier	OECD Guideline 202
	Algae toxicity	NOEC NOEL > 100 mg/l	3 d	Pseudokirchneriella subcapitata	ECHA Dossier	
	Crustacea toxicity	NOEC NOEL > 10 mg/l	21 d	Daphnia magna (Big water flea)	ECHA Dossier	OECD Guideline 211
68937-96-2	Polysulfides, di-tert-Bu					

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 12 of 18

	Acute algae toxicity	ErC50 > 100 (EL50) mg/l	72 h	Pseudokirchneriella subcapitata	ECHA Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 63 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD Guideline 202
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)						
	Acute fish toxicity	LC50 ca. 8,5 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 6,4 mg/l	96 h	Raphidocelis subcapitata	ECHA Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 ca. 91,4 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD Guideline 202
	Acute bacteria toxicity	EC50 ca. 2433 mg/l ()	3 h	activated sludge, domestic	ECHA Dossier	OECD Guideline 209
597-82-0	O,O,O-Triphenyl phosphorothioate					
	Acute fish toxicity	LL50 >100 mg/l	96 h	Danio rerio	ECHA Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 (loading rate WAF) mg/l	72 h	Desmodesmus subspicatus	ECHA Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 >100 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD Guideline 202
	Fish toxicity	NOEC 0,0017 mg/l	97 d	Oncorhynchus mykiss	ECHA Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC 0,00724 mg/l	21 d	Daphnia magna	ECHA Dossier	OECD Guideline 211
13703-82-7	Magnesium metaborate					
	Acute fish toxicity	LL50 >50 mg/l	96 h	Oncorhynchus mykiss		OECD Guideline 203
	Acute algae toxicity	ErC50 >50 mg/l	72 h	Pseudokirchneriella subcapitata		OECD Guideline 201
	Acute crustacea toxicity	EL50 >50 mg/l	48 h	Daphnia magna		OECD Guideline 202

12.2. Persistence and degradability

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 13 of 18

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			
	OECD Guideline 301 F	31%	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).			
68937-96-2	Polysulfides, di-tert-Bu			
	OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C	13 %	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).			
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)			
	ASTM D-5864-95	3,6%	28	ECHA Dossier
	not readily degradable			
597-82-0	O,O,O-Triphenyl phosphorothioate			
	OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C	17,8-19,3%	29	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).			
13703-82-7	Magnesium metaborate			
	OECD Guideline 301 B	4%	28	
	Not easily bio-degradable (according to OECD-criteria).			

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	> 3,5
68937-96-2	Polysulfides, di-tert-Bu	5,6
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	< 0,3
597-82-0	O,O,O-Triphenyl phosphorothioate	5

BCF

CAS No	Chemical name	BCF	Species	Source
68937-96-2	Polysulfides, di-tert-Bu	0,006	Lepomis macrochirus	ECHA Dossier
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	436	Onchorhynchus mykiss	ECHA Dossier
597-82-0	O,O,O-Triphenyl phosphorothioate	98	Fish	

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The mixture contains the following substances fulfilling the PBT criteria according to REACH , annex XIII:

O,O,O-Triphenyl phosphorothioate.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.6. Endocrine disrupting properties

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 14 of 18

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 3082

14.2. UN proper shipping name:ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(O,O,O-Triphenyl phosphorothioate)**14.3. Transport hazard class(es):**


9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

-

Inland waterways transport (ADN)**14.1. UN number or ID number:**

UN 3082

14.2. UN proper shipping name:ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(O,O,O-Triphenyl phosphorothioate)**14.3. Transport hazard class(es):**

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 15 of 18

Special Provisions: 274 335 375 601
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (O,O,O-Triphenyl phosphorothioate)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Marine pollutant: YES
 Special Provisions: 274, 335, 969
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (O,O,O-Triphenyl phosphorothioate)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Special Provisions: A97 A158 A197 A215
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y964
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 964
 IATA-max. quantity - Passenger: 450 L
 IATA-packing instructions - Cargo: 964
 IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



14.6. Special precautions for user

Informations for safe handling see chapter 7.
 Informations for personal protective equipment see chapter 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 16 of 18

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2010/75/EU on industrial emissions:

No information available.

Directive 2004/42/EC on VOC in paints and varnishes:

No information available.

Information according to Directive 2012/18/EU (SEVESO III):

E2 Hazardous to the Aquatic Environment

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)

REACH 1907/2006 Appendix XVII, No (mixture): 3, 75

Observe in addition any national regulations!

National regulatory information

Water hazard class (D):

2 - obviously hazardous to water

Additional information

Regulation (EU) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals: not relevant

15.2 Chemical Safety Assessment
not applicable.**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s):

2,3,4,5,6,7,8,10,11,12,13,14,15,16.

Rev. : 1,0 - 02.02.2024

Rev.: 2,0 - 03.02.2025, Changes in chapter: 3.2, 16

Rev.: 2,1 - 10.03.2025, Changes in chapter: 2.2, 2.3, 3.2, 4.1, 8.1, 11.1, 12.1, 12.2, 12.3, 12.5, 14, 15.1, 16

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 17 of 18

Abbreviations and acronyms

Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Eye Irrit: Eye irritation
Skin Sens: Skin sensitisation
Aquatic Chronic: Chronic aquatic hazard
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
LOAEL: Lowest observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level
NOAEC: No observed adverse effect concentration
NTP: National Toxicology Program
N/A: not applicable
PNEC: predicted no effect concentration
PBT: Persistent bioaccumulative toxic
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
SVHC: substance of very high concern
UN: United Nations
TSCA: Toxic Substances Control Act
VOC: Volatile Organic Compounds
WGK: Water Hazard Class (Germany)

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008**[CLP]**

Classification	Classification procedure
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Polysulfides, di-tert-Bu, Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched), Magnesium metaborate. May produce an allergic reaction.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:
Health hazards: Calculation method.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Getriebefluid SBL 75W-90

Revision date: 10.03.2025

Page 18 of 18

Environmental hazards: Calculation method.

Physical hazards: On basis of test data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)