

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SRS Getriebefluid HGS 75W-90**

Revision: 04.06.2026

Page 1 of 19

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

SRS Getriebefluid HGS 75W-90

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

gear oil

**Uses advised against**

No information available.

**1.3. Details of the supplier of the safety data sheet**

Company name: SRS Schmierstoff Vertrieb GmbH  
Street: Neuenkirchener Straße 8  
Place: D-48497 Salzbergen  
Telephone: 05976 - 945-0  
Responsible Department: Abt. Produktsicherheit: info.reach@srs-oil.de

**1.4. Emergency telephone number:**

Gift-Informationszentrum Nord (Göttingen) - Telefon 0551-19240

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**P273 Avoid release to the environment.  
P501 On basis of test data and / or calculated and / or estimated.**Special labelling**

EUH208 Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate. May produce an allergic reaction.

**2.3. Other hazards**

This mixture contains no substances of very high concern (SVHC) (&gt;0,1%) which are included in the Candidate List according to Article 59 of REACH.

For information or further instructions, see also section 11 or 12.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			65 - < 70 %
	265-159-2	649-469-00-9	01-2119480132-48	

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### SRS Getriebefluid HGS 75W-90

Revision: 04.06.2026

Page 2 of 19

	Asp. Tox. 1; H304		
157707-86-3	Dec-1-ene, trimers, hydrogenated		10 - < 12 %
	500-393-3	01-2119493949-12	
	Asp. Tox. 1; H304		
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified		7 - < 10 %
	265-158-7	649-468-00-3	01-2119487077-29
	Asp. Tox. 1; H304		
68511-50-2	1-Propene, 2-methyl-, sulfurized		3 - < 5 %
	270-943-2		
	Aquatic Chronic 4; H413		
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**		0.2 - < 0.3 %
	201-297-1	607-035-00-6	
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335		
68955-53-3	Amines, C12-14-tert-alkyl		0.1 - < 0.2 %
	701-175-2	01-2119456798-18	
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H302 H314 H317 H400 H410		
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines		< 0.1 %
	627-034-4	01-2119473797-19	
	Acute Tox. 4, Skin Corr. 1B, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H335 H373 H304 H400 H410		

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-56-9	265-159-2	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	65 - < 70 %
	inhalation: LC50 = >5,53 mg/l (dusts or mists); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg		
157707-86-3	500-393-3	Dec-1-ene, trimers, hydrogenated	10 - < 12 %
	inhalation: LC50 = >5,2 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg		
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	7 - < 10 %
	inhalation: LC50 = > 5,53 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
68511-50-2	270-943-2	1-Propene, 2-methyl-, sulfurized	3 - < 5 %
	oral: LD50 = 5000 mg/kg		
80-62-6	201-297-1	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**	0.2 - < 0.3 %
	inhalation: LC50 = 29,8 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 8400 mg/kg		
68955-53-3	701-175-2	Amines, C12-14-tert-alkyl	0.1 - < 0.2 %
	inhalation: LC50 = 1,19 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 251 mg/kg; oral: LD50 = 552 mg/kg Skin Sens. 1A; H317: >= 5 - 100		
1213789-63-9	627-034-4	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	< 0.1 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 1200 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10		

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SRS Getriebefluid HGS 75W-90**

Revision: 04.06.2026

Page 3 of 19

**Further Information**

\*\*Substance for which a community occupational exposure limit value applies in the European Union.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**After inhalation**

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, seek medical treatment.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

If swallowed or in the event of vomiting, risk of entering the lungs.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Sand. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder. In case of major fire and large quantities: Water spray jet. Water mist.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Burning produces heavy smoke.

In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>) Sulphur dioxide (SO<sub>2</sub>) Nitrogen oxides (NO<sub>x</sub>)

**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Co-ordinate fire-fighting measures to the fire surroundings.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Ventilate affected area.

Special danger of slipping by leaking/spilling product.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### SRS Getriebefluid HGS 75W-90

Revision: 04.06.2026

Page 4 of 19

**For non-emergency personnel**

Wear personal protection equipment (refer to section 8).

**For emergency responders**

No special measures are necessary.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil. If required, notify relevant authorities according to all applicable regulations.

**6.3. Methods and material for containment and cleaning up****For containment**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Treat the recovered material as prescribed in the section on waste disposal.  
Clean contaminated articles and floor according to the environmental legislation.

**6.4. Reference to other sections**

No information available.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Wear suitable protective clothing. ( See section 8. )  
Avoid formation of oil dust.

**Advice on protection against fire and explosion**

Usual measures for fire prevention. Keep away from sources of ignition - No smoking.  
Fire class B

**Advice on general occupational hygiene**

Clean skin thoroughly after working.  
Do not put any product-impregnated cleaning rags into your trouser pockets.

**Further information on handling**

Do not breathe vapour/aerosol.  
Avoid contact with eyes and skin.  
General protection and hygiene measures: See section 8.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

**Hints on joint storage**

Do not store together with: Gas. Explosives. Oxidizing substances. Radioactive substances. Infectious substances

**Further information on storage conditions**

Temperature control required. Protect from light. Keep container tightly closed. Do not allow contact with air.

**7.3. Specific end use(s)**

See section 1.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limit values**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### SRS Getriebefluid HGS 75W-90

Revision: 04.06.2026

Page 5 of 19

CAS No	Name of agent	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
80-62-6	Methyl methacrylate	50	-		TWA (8 h)	
		100	-		STEL (15 min)	

#### DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>	
Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>	
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>	
Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>	
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day	
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>	
68955-53-3	Amines, C12-14-tert-alkyl			
Consumer DNEL, long-term	inhalation	systemic	2,5 mg/m <sup>3</sup>	
Consumer DNEL, long-term	inhalation	local	1,2 mg/m <sup>3</sup>	
Worker DNEL, long-term	inhalation	systemic	12,5 mg/m <sup>3</sup>	
Worker DNEL, long-term	inhalation	local	12,1 mg/m <sup>3</sup>	
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines			
Worker DNEL, long-term	inhalation	systemic	0,38 mg/m <sup>3</sup>	
Worker DNEL, long-term	inhalation	local	1 mg/m <sup>3</sup>	
Worker DNEL, acute	inhalation	local	1 mg/m <sup>3</sup>	
Consumer DNEL, long-term	inhalation	systemic	0,035 mg/m <sup>3</sup>	
Consumer DNEL, long-term	oral	systemic	0,04 mg/kg bw/day	

#### PNEC values

CAS No	Name of agent	Value
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
68955-53-3	Amines, C12-14-tert-alkyl	

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### SRS Getriebefluid HGS 75W-90

Revision: 04.06.2026

Page 6 of 19

Freshwater	0,001 mg/l
Freshwater (intermittent releases)	0,004 mg/l
Marine water	0 mg/l
Freshwater sediment	2,14 mg/kg
Marine sediment	0,214 mg/kg
Secondary poisoning	4,71 mg/kg
Microorganisms in sewage treatment plants (STP)	0,635 mg/l
Soil	0.428 mg/kg
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines
Freshwater	0,00026 mg/l
Freshwater (intermittent releases)	0,0016 mg/l
Marine water	0,000026 mg/l
Freshwater sediment	3,76 mg/kg
Marine sediment	0,376 mg/kg
Microorganisms in sewage treatment plants (STP)	0,55 mg/l
Soil	10 mg/kg

#### Additional advice on limit values

Air limit values:

Possibility of exposure to Aerosol (Mineral oil )

Limit value (TLV-TWA ) = 5 mg/ m3 - Source: ACGIH

Limit value (TLV-STEL ) = 10 mg/ m3 - Source: ACGIH

STEL: short-term exposure limits

TLV: Threshold Limiting Value

TWA: time weighted average

ACGIH: American Conference of Governmental Industrial Hygienists

#### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Safety goggles with side protection. In case of increased risk add protective face shield. EN 166

##### Hand protection

Use safety gloves of following materials: NBR (nitrile) / neopren / viton (permeationslevel 5 - 6), Cat. II according to norm EN 374/EN 388.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Gloves must be periodically inspected and changed in case of wear, perforations or contaminations.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

##### Skin protection

Oil-resistant and hardly inflammable protective clothing.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SRS Getriebefluid HGS 75W-90**

Revision: 04.06.2026

Page 7 of 19

**Respiratory protection**

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

-aerosol or mist formation

-Exceeding exposure limit values

Suitable respiratory protection apparatus: Respiratory equipment in case of nebulosity or aerosol: Use a mask with a filter type A2, A2/P2 or ABEK.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

**Environmental exposure controls**

No information available.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	clear
Odour:	characteristic

	Test method
Melting point/freezing point:	No information available.
Boiling point or initial boiling point and boiling range:	No information available.
Flammability:	No information available.
Lower explosion limits:	No information available.
Upper explosion limits:	No information available.
Flash point:	210 °C DIN EN ISO 2592
Auto-ignition temperature:	No information available.
Decomposition temperature:	No information available.
pH-Value:	No information available.
Viscosity / kinematic: (at 40 °C)	75,8 mm <sup>2</sup> /s DIN EN ISO 3104
Water solubility:	practically insoluble
Solubility in other solvents	No information available.
Partition coefficient n-octanol/water:	No information available.
Vapour pressure: (at 20 °C)	<0,1 hPa calculated.
Vapour pressure: (at 50 °C)	No information available.
Density (at 15 °C):	0,879 g/cm <sup>3</sup> DIN 51757
Bulk density:	No information available.
Relative vapour density:	No information available.
Particle characteristics:	No information available.

**9.2. Other information****Information with regard to physical hazard classes**

Explosive properties	
none	
Sustained combustibility:	No data available
Self-ignition temperature	
Solid:	No information available.
Gas:	No information available.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SRS Getriebefluid HGS 75W-90**

Revision: 04.06.2026

Page 8 of 19

Oxidizing properties  
none

**Other safety characteristics**

Evaporation rate:	No information available.
Solvent separation test:	No information available.
Solvent content:	No information available.
Solid content:	No information available.
Sublimation point:	No information available.
Softening point:	No information available.
Pour point:	-48 °C ASTM D 5985
Viscosity / dynamic:	No information available.
Flow time:	No information available.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

The mixture is chemically stable under recommended conditions of storage, use and temperature.

**10.3. Possibility of hazardous reactions**

No hazardous reactions known.  
Refer to chapter 10.5.

**10.4. Conditions to avoid**

No information available.

**10.5. Incompatible materials**

Oxidising agent, strong

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

No information available.

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 5000 mg/kg; ATE (inhalation vapour) &gt; 50 mg/l; ATE (inhalation dust/mist) &gt; 12,5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified				
	oral	LD50 >5000 mg/kg	Rat.	ECHA Dossier	
	dermal	LD50 >5000 mg/kg	Rabbit.	ECHA Dossier	
	inhalation (4 h) dust/mist	LC50 >5,53 mg/l	Rat.	ECHA Dossier	
157707-86-3	Dec-1-ene, trimers, hydrogenated				

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### SRS Getriebefluid HGS 75W-90

Revision: 04.06.2026

Page 9 of 19

	oral	LD50 mg/kg	>5000	Rat.	ECHA Dossier	
	dermal	LD50 mg/kg	>2000	Rat.	ECHA Dossier	
	inhalation (4 h) dust/mist	LC50	>5,2 mg/l	Rat.	ECHA Dossier	OECD 403
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified					
	oral	LD50 mg/kg	> 5000	Rat	ECHA Dossier	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rabbit	ECHA Dossier	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 mg/l	> 5,53	Rat	ECHA Dossier	OECD Guideline 403
68511-50-2	1-Propene, 2-methyl-, sulfurized					
	oral	LD50 mg/kg	5000	Rat	MSDS external	
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**					
	oral	LD50 mg/kg	8400	Rat		
	dermal	LD50 mg/kg	> 5000	Rabbit	ECHA Dossier	
	inhalation (4 h) dust/mist	LC50	29,8 mg/l	Rat	ECHA Dossier	
68955-53-3	Amines, C12-14-tert-alkyl					
	oral	LD50 mg/kg	552	Rat	ECHA Dossier	OECD 401
	dermal	LD50 mg/kg	251	Rat	ECHA Dossier	OECD 402
	inhalation (4 h) vapour	LC50	1,19 mg/l	Rat	ECHA Dossier	OECD 403
	inhalation dust/mist	ATE	0,05 mg/l			
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines					
	oral	LD50 mg/kg	1200	Rat	REACH Dossier	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rat	REACH Dossier	OECD Guideline 402

#### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### SRS Getriebefluid HGS 75W-90

Revision: 04.06.2026

Page 10 of 19

Based on available data, the classification criteria are not met.

Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate. May produce an allergic reaction.

Skin sensitisation:

Amines, C12-14-tert-alkyl (Conc.= 5%)

Test results: not sensitizing. Method: Buehler Method OECD 406, Species: Guinea-pig. Literature information: Manufacturer

May cause sensitisation especially in sensitive humans.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified:

In vitro mutagenicity/genotoxicity:

Method: OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test), OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test), OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative Literature information: REACH Dossier; Chronic dermal toxicity: Exposure time: ~546 d; Species: Mouse.; Method: OECD Guideline 451; Result: Carcinogenicity = negative Literature information: REACH Dossier; Reproductive toxicity: Exposure route: oral. Species: Rat.; Method: OECD Guideline 421; Result: NOAEL >1000 mg/kg; Literature information: REACH Dossier; Developmental toxicity/teratogenicity: Exposure route: dermal. Species: Rat.; Method: OECD Guideline 414; Result: NOAEL >2000 mg/kg; Literature information: REACH Dossier

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified:

In vitro mutagenicity/genotoxicity:

Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay) with modifications

Results: negative / positive

Method: OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

Results: negative

Method: OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Results: negative / positive

Literature information: REACH Dossier

In vivo mutagenicity/genotoxicity

Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Results: negative ; Literature information: REACH Dossier

Reproductive toxicity

Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

Exposure time: 28d; Species: Rat

Results: NOAEL = > 2000 mg/kg(bw)/day; Literature information: REACH Dossier

Developmental toxicity/teratogenicity:

Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study)

Exposure time: 28d; Species: Rat

Results: NOAEL = > 2000 mg/kg(bw)/day; Literature information: REACH Dossier

Dec-1-ene, trimers, hydrogenated:

In vitro mutagenicity/genotoxicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative Literature information: REACH Dossier; Reproductive toxicity: Species: Rat; Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test); Result: NOAEL > 1000 mg/kg; Literature information: REACH Dossier

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate:

In-vitro mutagenicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative Literature information: REACH Dossier; Carcinogenicity: negative Method: OECD Guideline 451 (Carcinogenicity Studies, 6h/d); Species: Rat,oral.; Exposure duration: 2 years; Result: NOAEC >= 2000 ppm; Literature information: REACH Dossier; Reproductive toxicity: Method: OECD Guideline 416

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SRS Getriebefluid HGS 75W-90**

Revision: 04.06.2026

Page 11 of 19

(Two-Generation Reproduction Toxicity Study); Species: Rat; Result: NOAEL = 400 mg/kg; Literature information: REACH Dossier; 1. Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Species: Rabbit.

Exposure duration: 28d; Result: NOAEL = 450 mg/kg

2. Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Species: Rat; Result: NOAEC  $\geq$  8,3 mg/l ; Literature information: REACH Dossier

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:

In-vitro mutagenicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay) (reliability scoring based on 1997 guideline), OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test): OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test); Results: negative; Literature information: REACH Dossier

Developmental toxicity/teratogenicity: Method: 40 CFR Part 798.4700; Species: Rat; Result: NOAEL > 80 mg/kg; Species: Rabbit ; Result: NOAEL > 30 mg/kg; Literature information: REACH Dossier

Amines, C12-14-tert-alkyl:

In-vitro mutagenicity:

Method:

-OECD Guideline 471 (Bacterial Reverse Mutation Assay)

-OECD Guideline 476 (In Vitro Mammalian Cell Gene Mutation Test)

Result: negative

Literature information: REACH Dossier

In vivo mutagenicity/genotoxicity:

Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Species: Mouse.

Results: negative

Literature information: REACH Dossier

Reproductive toxicity:

Species: Rat.

Method: OECD Guideline 415

Result: NOAEL(F1)  $\geq$  511 < 511 ppm (Symptoms/ delayed effects: body weight)

Developmental toxicity/teratogenicity:

Exposure time: 21d, dermal.

Species: Rat.

Method: OECD Guideline 414

Result: NOAEL (Maternal toxicity) = 5 mg/kg bw/day; NOAEL (fetus) = 45 mg/kg bw/day

Literature information: REACH Dossier

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified:

Subchronic oral toxicity: Exposure time: 90d; Species: Sprague-Dawley Rat.; Method: OECD Guideline 408;

Result: LOAEL = 125 mg/kg; Literature information: REACH Dossier;

Subacute inhalative toxicity :

Exposure time: 28d; Species: Sprague-Dawley Rat.; Result: NOAEC > 980 mg/m<sup>3</sup>; Literature information:

REACH Dossier; Subacute dermal toxicity: Exposure time: 28d; Species: Rabbit; Method: OECD Guideline

410; Result: NOAEL 1000 mg/kg; Literature information: REACH Dossier

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified:

Subacute inhalative toxicity : Method: -; Exposure time: 28d; Species: Rat; Results: NOAEL > 980 mg/m<sup>3</sup>;

Literature information: J Appl Toxicol, Vol 11(4), pp 297-302; Subacute dermal toxicity: Method: OECD

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SRS Getriebefluid HGS 75W-90**

Revision: 04.06.2026

Page 12 of 19

Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study); Exposure time: 28d; Species: Rabbit; Results: NOAEL 1000 mg/kg(bw)/day; Literature information: REACH Dossier; Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents); Species: Rat; Results: NOAEL = 125 mg/kg; Literature information: REACH Dossier

Dec-1-ene, trimers, hydrogenated:

Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Species: Rat; Results: NOAEL 1000 mg/kg; Literature information: REACH Dossier

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate:

Chronic oral toxicity: Method: -; Species: Rat; Exposure duration: 2 years; Results: NOAEL = 2000 ppm. Literature information: REACH Dossier; 1. Chronic inhalation toxicity: Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies, 6h/d); Species: Rat; Exposure duration: approx. 2 years; Results: LOAEC = 250 ppm.

2. Chronic inhalation toxicity: Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies, 6h/d); Species: Rat; Exposure duration: approx. 2 years; Results: NOAEC = 1,64 m/l; Literature information: REACH Dossier

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:

Subacute oral toxicity:

Method: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

Species: Rat; Exposure duration: 28 d

Results: NOAEL = 3,25 mg/kg; Literature information: REACH Dossier

Amines, C12-14-tert-alkyl:

Subchronic inhalative toxicity:

Method: OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)

Species: Rat

Results: NOAEC = 19 mg/m<sup>3</sup>

Literature information: REACH Dossier

Subacute dermal toxicity

Method: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Species: Rat

Results: NOAEL = 20 mg/kg

Literature information: REACH Dossier

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Endocrine disrupting properties**

Based on available data, the classification criteria are not met.

This product does not contain a substance (> 0,1 %) that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Other information**

Frequently or prolonged contact with skin may cause dermal irritation.

**SECTION 12: Ecological information****12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified						



### Safety Data Sheet

according to Regulation (EC) No 1907/2006

#### SRS Getriebefluid HGS 75W-90

Revision: 04.06.2026

Page 13 of 19

	Acute fish toxicity	LC50 mg/l	>100	96 h	Pimephales promelas	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l	>10000	48 h	Daphnia magna	ECHA Dossier	
	Crustacea toxicity	NOEC	10 mg/l	21 d	Daphnia magna	ECHA Dossier	
157707-86-3	Dec-1-ene, trimers, hydrogenated						
	Acute fish toxicity	LL50 mg/l	>1000	96 h	Pimephales promelas	ECHA Dossier	USEPA (1975)
	Acute crustacea toxicity	EL50 mg/l	>1000	48 h	Daphnia magna	ECHA Dossier	OECD Guideline 202
	Crustacea toxicity	NOEC	125 mg/l	21 d	Daphnia magna	ECHA Dossier	OECD Guideline 211
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified						
	Acute fish toxicity	LC50 100 mg/l	LL50 >	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier	OECD Guideline 203
	Acute crustacea toxicity	EC50 >10000 mg/l	EL50	48 h	Daphnia magna (Big water flea)	ECHA Dossier	OECD Guideline 202
	Algae toxicity	NOEC 100 mg/l	NOEL >	3 d	Pseudokirchnerella subcapitata	ECHA Dossier	
	Crustacea toxicity	NOEC 10 mg/l	NOEL >	21 d	Daphnia magna (Big water flea)	ECHA Dossier	OECD Guideline 211
68511-50-2	1-Propene, 2-methyl-, sulfurized						
	Acute fish toxicity	LC50 mg/l	250-500	96 h	Pimephales promelas	MSDS external	
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna	MSDS external	
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**						
	Acute fish toxicity	LC50	410 mg/l	96 h	Pimephales promelas	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	>110	72 h	Pseudokirchnerella subcapitata (OECD 201)	ECHA Dossier	
	Acute crustacea toxicity	EC50	720 mg/l	48 h	Daphnia magna	ECHA Dossier	
68955-53-3	Amines, C12-14-tert-alkyl						
	Acute fish toxicity	LC50	1,3 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	0,44	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	OECD 201
	Acute crustacea toxicity	EC50	4,1 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,078	96 d	Oncorhynchus mykiss	ECHA Dossier	OECD Guideline 210
	Acute bacteria toxicity	EC50 mg/l ( )	63,5	0,5 h	activated sludge of a predominantly domestic sewage	ECHA Dossier	OECD Guideline 209

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### SRS Getriebefluid HGS 75W-90

Revision: 04.06.2026

Page 14 of 19

1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines					
	Acute fish toxicity	LC50 mg/l	0,06	96 h	Pimephales promelas	REACH Dossier EPA OPPTS 850.1085
	Acute algae toxicity	ErC50 mg/l	0,38	72 h	Desmodesmus subspicatus	REACH Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,98	48 h	Daphnia magna	REACH Dossier OECD Guideline 202
	Crustacea toxicity	NOEC mg/l	0,013	21 d	Daphnia magna	REACH Dossier OECD Guideline 211
	Acute bacteria toxicity	EC50 mg/l ( )	222,5	3 h	activated sludge	REACH Dossier OECD Guideline 209

### 12.2. Persistence and degradability

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified				
	OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C		2-4%	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).				
157707-86-3	Dec-1-ene, trimers, hydrogenated				
	OECD 301D / EEC 92/69 annex V, C.4-E		2 %	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).				
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified				
	OECD Guideline 301 F		31%	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).				
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**				
	OECD 301C / ISO 9408 / EWG 92/69 Anhang V, C.4-F		94%	14	ECHA Dossier
	Readily biodegradable (according to OECD criteria).				
68955-53-3	Amines, C12-14-tert-alkyl				
	OECD 301D / EEC 92/69 annex V, C.4-E		22 %	28	ECHA Dossier
	Not readily biodegradable (according to OECD criteria)				
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines				
	OECD Guideline 301 D		66%	28	REACH Dossier
	Readily biodegradable (according to OECD criteria).				

### 12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
157707-86-3	Dec-1-ene, trimers, hydrogenated	>6,5
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	> 3,5
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate**	1,32
68955-53-3	Amines, C12-14-tert-alkyl	2,9
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	5,16

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SRS Getriebefluid HGS 75W-90**

Revision: 04.06.2026

Page 15 of 19

**BCF**

CAS No	Chemical name	BCF	Species	Source
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	173		Environmental Toxico

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

Based on available data, the classification criteria are not met.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

**12.6. Endocrine disrupting properties**

Based on available data, the classification criteria are not met.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

**12.7. Other adverse effects**

No information available.

**Further information**

Ozone depletion potential (ODP): No information available.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**List of Wastes Code - contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 9006
<b>14.2. UN proper shipping name:</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
<b>14.3. Transport hazard class(es):</b>	9
<b>14.4. Packing group:</b>	-
Hazard label:	-
Classification code:	M12

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	No dangerous good in sense of this transport regulation.
--------------------------------------	--

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SRS Getriebefluid HGS 75W-90**

Revision: 04.06.2026

Page 16 of 19

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Informations for safe handling see chapter 7.

Informations for personal protective equipment see chapter 8.

**14.7. Maritime transport in bulk according to IMO instruments**

not relevant

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

**Additional information**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No (mixture): 3, 75

Observe in addition any national regulations!

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**Additional information**

Regulation (EU) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals: not relevant

15.2 Chemical Safety Assessment  
not applicable.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 15,16.

Rev.: 1,0 - 13.04.2015

Rev.: 1,01 - 28.04.2015

Rev.: 1,1 - 10.05.2016



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### SRS Getriebefluid HGS 75W-90

Revision: 04.06.2026

Page 17 of 19

Rev : 2,0 - 02.06.2017

Rev.: 3,0 - 27.06.2018

Rev.: 4,0 - 26.06.2019

Rev.: 5,0 - 29.06.2020; Changes in chapter: 2.2, 3.2, 11.1, 15.1, 16

Rev.: 6.0 - 04.06.2021 Changes in chapter: 3.2, 6.1, 6.3, 11.2, 12.6, 12.7, 15.1, 16

Rev.: 7.0 - 14.06.2022, Changes in chapter: 2.3, 8.2, 12.1, 12.5, 12.6, 16

Rev.: 7.1 - 01.03.2023, Changes in chapter: 2.3, 3.2, 8.1, 9.1, 11.1, 12.1, 12.2, 12.3, 12.5, 15.1, 16

Rev.: 8.0 - 05.03.2024, Changes in chapter: 8.1, 11.2, 12.1, 12.7, 14, 15.1, 16

Rev.: 9.0 - 04.03.2025, Changes in chapter: 11.1, 16

Rev.: 10.0 - 16.02.2026, Changes in chapter: 15.1, 16

Rev.: 10,1 - 04.06.2026, Changes in chapter: 3.2, 8.1, 11.1, 11.2, 12.1, 12.2, 12.3, 15.1, 16

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SRS Getriebefluid HGS 75W-90**

Revision: 04.06.2026

Page 18 of 19

**Abbreviations and acronyms**

Flam. Liq. 2: Flammable liquids, hazard category 2  
Acute Tox. 2: Acute toxicity, hazard category 2  
Acute Tox. 3: Acute toxicity, hazard category 3  
Acute Tox. 4: Acute toxicity, hazard category 4  
Asp. Tox. 1: Aspiration hazard, hazard category 1  
Skin Corr. 1B: Skin corrosion, sub-category 1B  
Skin Irrit. 2: Skin irritation, hazard category 2  
Skin Sens. 1: Skin sensitisation, hazard category 1  
Skin Sens. 1A: Skin sensitisation, hazard category 1A  
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3  
STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2  
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1  
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1  
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3  
Aquatic Chronic 4: Hazardous to the aquatic environment, long-term hazard category: Chronic 4  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
CAS: Chemical Abstracts Service  
CLP: Classification, Labelling and Packaging of substances and mixtures  
d: day(s)  
DNEL: Derived No Effect Level  
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER  
EINECS: European INventory of Existing Commercial chemical Substances  
ELINCS: European List of Notified Chemical Substances  
ECHA: European Chemicals Agency  
EWC: European Waste Catalogue  
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organization  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
h: hour  
LOAEL: Lowest observed adverse effect level  
LOAEC: Lowest observed adverse effect concentration  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
NOAEL: No observed adverse effect level  
NOAEC: No observed adverse effect concentration  
NLP: No-Longer Polymers  
NTP: National Toxicology Program  
N/A: not applicable  
OECD: Organisation for Economic Co-operation and Development  
PNEC: predicted no effect concentration  
PBT: Persistent bioaccumulative toxic  
PMT: Persistent, mobile and toxic  
REACH: Registration, Evaluation, Authorisation of Chemicals  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail )  
SVHC: substance of very high concern  
TRGS: Technische Regeln für Gefahrstoffe  
UN: United Nations

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SRS Getriebefluid HGS 75W-90**

Revision: 04.06.2026

Page 19 of 19

TSCA: Toxic Substances Control Act  
vPvM: very persistent and very mobile  
vPvB: very persistent and very bioaccumulative  
VOC: Volatile Organic Compounds  
WGK: Water Hazard Class (Germany)

**Key literature references and sources for data**

<https://echa.europa.eu/>  
<https://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp>  
<https://cfpub.epa.gov/ecotox/search.cfm>  
<http://www.inchem.org/#/search>  
<https://pubchem.ncbi.nlm.nih.gov/>  
<http://ccinfoweb.ccohs.ca/rtecs/search.html>  
<https://webrigoletto.uba.de/rigoletto/>

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H330 Fatal if inhaled.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
H413 May cause long lasting harmful effects to aquatic life.  
EUH208 Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate. May produce an allergic reaction.

**Further Information**

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:  
Health hazards: Calculation method.  
Environmental hazards: Calculation method.  
Physical hazards: On basis of test data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*