

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 1 of 22

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SRS Wiolan HV 15

UFI: GXXG-M7QT-1306-XS65

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hydraulic fluids

Uses advised against

none

1.3. Details of the supplier of the safety data sheet

Company name: SRS Schmierstoff Vertrieb GmbH

Street: Neuenkirchener Straße 8

Place: D-48497 Salzbergen

Telephone: 05976 - 945-0

Responsible Department: Abt. Produktsicherheit: info.reach@srs-oil.de

1.4. Emergency telephone number:

Further Information

Worldwide emergency information service: GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified

Signal word: Danger

Pictograms:



Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to local/regional/national/international regulations.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 2 of 22

2.3. Other hazards

This mixture contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

For information or further instructions, see also section 11 or 12.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			50 - < 55 %
	265-159-2	649-469-00-9	01-2119480132-48	
	Asp. Tox. 1; H304			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			
	265-158-7	649-468-00-3	01-2119487077-29	
	Asp. Tox. 1; H304			
128-39-2	2,6-di-tert-butylphenol			
	204-884-0		01-2119490822-33	
	Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic 1; H315 H400 H410			
104-76-7	2-ethylhexan-1-ol*			
	203-234-3		01-2119487289-20	
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Aquatic Chronic 3; H332 H315 H319 H335 H412			
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*			
	201-297-1	607-035-00-6	01-2119452498-28	
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			
108-88-3	toluene*			
	203-625-9	601-021-00-3		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304			
108-95-2	phenol; carbolic acid; monohydroxybenzene; phenylalcohol*			
	203-632-7	604-001-00-2		
	Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, STOT RE 2; H341 H331 H311 H301 H314 H373			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 3 of 22

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
Specific Conc. Limits, M-factors and ATE			
64742-56-9	265-159-2	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	50 - < 55 %
inhalation: LC50 = >5,53 mg/l (dusts or mists); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg			
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	45 - < 50 %
inhalation: LC50 = > 5,53 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg			
128-39-2	204-884-0	2,6-di-tert-butylphenol	0.2 - < 0.3 %
dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg			
104-76-7	203-234-3	2-ethylhexan-1-ol*	< 0.1 %
inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 4,3 mg/l (dusts or mists); dermal: LD50 = >3000 mg/kg; oral: LD50 = 2047 mg/kg			
80-62-6	201-297-1	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*	< 0.1 %
inhalation: LC50 = 29,8 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = >5000 mg/kg			
108-88-3	203-625-9	toluene*	< 0.1 %
inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg			
108-95-2	203-632-7	phenol; carboxylic acid; monohydroxybenzene; phenylalcohol*	< 0.1 %
inhalation: ATE = 3 mg/l (vapours); inhalation: LC50 = >0,9 (8h) mg/l (dusts or mists); dermal: LD50 = 660 mg/kg; oral: LD50 = 282 mg/kg Skin Corr. 1B; H314: >= 3 - 100 Skin Irrit. 2; H315: >= 1 - < 3 Eye Irrit. 2; H319: >= 1 - < 3			

Further Information

*Substance for which a community occupational exposure limit value applies in the European Union.

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London).

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Observe risk of aspiration if vomiting occurs. Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.



Safety Data Sheet

SRS Schmierstoff Vertrieb GmbH

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 4 of 22

4.2. Most important symptoms and effects, both acute and delayed

If swallowed or in the event of vomiting, risk of entering the lungs.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Sand. Foam. Carbon dioxide (CO2). Extinguishing powder. In case of major fire and large quantities:
Water spray jet. Water mist.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO2) Sulphur dioxide (SO2)
Nitrogen oxides (NOx)

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ventilate affected area.
Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Wear personal protection equipment (refer to section 8).

For emergency responders

No special precautionary measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

No information available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling



Safety Data Sheet

SRS Schmierstoff Vertrieb GmbH

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 5 of 22

Advice on safe handling

Wear suitable protective clothing. (See section 8.)

Avoid formation of oil dust.

Advice on protection against fire and explosion

Usual measures for fire prevention. Keep away from sources of ignition - No smoking.

Fire class B

Advice on general occupational hygiene

Clean skin thoroughly after working.

Do not put any product-impregnated cleaning rags into your trouser pockets.

When using do not eat, drink or smoke.

Further information on handling

Do not breathe vapour/aerosol.

Avoid contact with eyes and skin.

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

Hints on joint storage

Do not store together with: Gas. Explosives. Oxidizing substances. Radioactive substances. Infectious substances

Further information on storage conditions

Temperature control required. Protect from light. Keep container tightly closed. Do not allow contact with air.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
104-76-7	2-Ethylhexan-1-ol	1	5.4		TWA (8 h)	
80-62-6	Methyl methacrylate	50	-		TWA (8 h)	
		100	-		STEL (15 min)	
108-95-2	Phenol	2	8		TWA (8 h)	
		4	16		STEL (15 min)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 6 of 22

DNEL/DMEL values

CAS No	Name of agent			
	DNEL type	Exposure route	Effect	Value
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			
	Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³
	Worker DNEL, long-term	inhalation	local	5,58 mg/m ³
	Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			
	Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³
	Worker DNEL, long-term	inhalation	local	5,58 mg/m ³
	Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³
128-39-2	2,6-di-tert-butylphenol			
	Worker DNEL, long-term	dermal	systemic	11,25 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	70,61 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic	20,9 mg/m ³
	Consumer DNEL, long-term	oral	systemic	6,75 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	6,75 mg/kg bw/day
104-76-7	2-ethylhexan-1-ol*			
	Worker DNEL, long-term	inhalation	systemic	12,8 mg/m ³
	Worker DNEL, long-term	inhalation	local	53,2 mg/m ³
	Worker DNEL, long-term	dermal	systemic	23 mg/kg bw/day
	Worker DNEL, acute	inhalation	local	53,2 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic	2,3 mg/m ³
	Consumer DNEL, long-term	inhalation	local	26,6 mg/m ³
	Consumer DNEL, acute	inhalation	local	26,6 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	11,4 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	1,1 mg/kg bw/day
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*			
	Worker DNEL, long-term	inhalation	local	208 mg/m ³
	Worker DNEL, long-term	inhalation	systemic	348,4 mg/m ³
	Worker DNEL, acute	inhalation	local	416 mg/m ³
	Worker DNEL, long-term	dermal	systemic	13,67 mg/kg bw/day
	Worker DNEL, long-term	dermal	local	1,5 mg/cm ²
	Worker DNEL, acute	dermal	local	1,5 mg/cm ²
	Consumer DNEL, long-term	inhalation	systemic	74,3 mg/m ³
	Consumer DNEL, long-term	inhalation	local	104 mg/m ³
	Consumer DNEL, acute	inhalation	local	208 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	8,2 mg/kg bw/day



Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Schmierstoff Vertrieb GmbH

SRS Wiolan HV 15

Revision: 12.01.2026

Page 7 of 22

Consumer DNEL, long-term	dermal	local	1,5 mg/cm ²
Consumer DNEL, long-term	oral	systemic	8,2 mg/kg bw/day
Consumer DNEL, acute	dermal	local	1,5 mg/cm ²

PNEC values

CAS No	Name of agent	
	Environmental compartment	Value
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	
	Secondary poisoning	9,33 mg/kg
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	
	Secondary poisoning	9,33 mg/kg
128-39-2	2,6-di-tert-butylphenol	
	Freshwater	0,001 mg/l
	Freshwater (intermittent releases)	0,004 mg/l
	Marine water	0,0001 mg/l
	Freshwater sediment	0,317 mg/kg
	Marine sediment	0,0317
	Secondary poisoning	60 mg/kg
	Micro-organisms in sewage treatment plants (STP)	10 mg/l
	Soil	0,679 mg/kg
104-76-7	2-ethylhexan-1-ol*	
	Freshwater	0,0278 mg/l
	Marine water	0,00278 mg/l
	Freshwater sediment	0,272 mg/kg
	Marine sediment	0,0272 mg/kg
	Micro-organisms in sewage treatment plants (STP)	10 mg/l
	Soil	0,038 mg/kg
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*	
	Freshwater	0,94 mg/l
	Freshwater (intermittent releases)	0,94 mg/l
	Marine water	0,094 mg/l
	Freshwater sediment	10,2 mg/kg
	Marine sediment	0,102 mg/kg
	Micro-organisms in sewage treatment plants (STP)	10 mg/l
	Soil	1,48 mg/kg

Additional advice on limit values

Air limit values:

Possibility of exposure to Aerosol (Mineral oil)

Limit value (TLV-TWA) = 5 mg/ m³ - Source: ACGIH

Limit value (TLV-STEL) = 10 mg/ m³ - Source: ACGIH

STEL: short-term exposure limits

TLV: Threshold Limiting Value

TWA: time weighted average

ACGIH:American Conference of Governmental Industrial Hygienists

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 8 of 22

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety goggles with side protection. In case of increased risk add protective face shield. EN 166

Hand protection

Use safety gloves of following materials: NBR (nitrile) / neopren / viton (permeationslevel 5 - 6), Cat. II according to norm EN 374/EN 388.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Gloves must be periodically inspected and changed in case of wear, perforations or contaminations.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Oil-resistant and hardly inflammable protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

-aerosol or mist formation

-Exceeding exposure limit values

Suitable respiratory protection apparatus: Respiratory equipment in case of nebulosity or aerosol: Use a mask with a filter type A2, A2/P2 or ABEK.

The filter class must be suitable for the maximum contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	clear
Odour:	characteristic

Test method

Melting point/freezing point: No information available.

Boiling point or initial boiling point and
boiling range: No information available.

Flammability: No information available.

Lower explosion limits: No information available.

Upper explosion limits: No information available.

Flash point: 171 °C COC

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 9 of 22

Auto-ignition temperature:	No information available.
Decomposition temperature:	No information available.
pH-Value:	No information available.
Viscosity / kinematic: (at 40 °C)	14,96 mm ² /s DIN EN ISO 3104
Water solubility:	Immiscible
Solubility in other solvents	
No information available.	
Partition coefficient n-octanol/water:	No information available.
Vapour pressure: (at 20 °C)	No information available.
Vapour pressure: (at 50 °C)	No information available.
Density (at 15 °C):	0,8785 g/cm ³ DIN 51757
Bulk density:	No information available.
Relative vapour density:	No information available.
Particle characteristics:	No information available.

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties	
none	
Sustained combustibility:	
No data available	
Self-ignition temperature	
Solid:	No information available.
Gas:	No information available.
Oxidizing properties	
none	

Other safety characteristics

Evaporation rate:	No information available.
Solvent separation test:	No information available.
Solvent content:	No information available.
Solid content:	No information available.
Sublimation point:	No information available.
Softening point:	No information available.
Pour point:	-45 °C ASTM D 5985
Viscosity / dynamic:	No information available.
Flow time:	No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

Refer to chapter 10.5.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 10 of 22

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 11 of 22

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified				
	oral	LD50 mg/kg	>5000 Rat.	ECHA Dossier	
	dermal	LD50 mg/kg	>5000 Rabbit.	ECHA Dossier	
	inhalation (4 h) dust/mist	LC50 mg/l	>5,53 mg/l Rat.	ECHA Dossier	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified				
	oral	LD50 mg/kg	> 5000 Rat	ECHA Dossier	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000 Rabbit	ECHA Dossier	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 mg/l	> 5,53 Rat	ECHA Dossier	OECD Guideline 403
128-39-2	2,6-di-tert-butylphenol				
	oral	LD50 mg/kg	>5000 Rat	ECHA Dossier	OECD 401
	dermal	LD50 mg/kg	>2000 Rat	ECHA Dossier	
104-76-7	2-ethylhexan-1-ol*				
	oral	LD50 mg/kg	2047 Rat.	ECHA Dossier	OECD Guideline 401
	dermal	LD50 mg/kg	>3000 Rat.	ECHA Dossier	OECD Guideline 402
	inhalation vapour	ATE mg/l	11 mg/l		
	inhalation (4 h) dust/mist	LC50 mg/l	4,3 mg/l Rat.	ECHA Dossier	OECD Guideline 403
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*				
	oral	LD50 mg/kg	>5000 Rat	ECHA Dossier	WoE
	dermal	LD50 mg/kg	> 5000 Rabbit	ECHA Dossier	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 mg/l	29,8 mg/l Rat	ECHA Dossier	
108-88-3	toluene*				
	oral	LD50 mg/kg	>5000 Rat	ECHA Dossier	EU Method B.1
	dermal	LD50 mg/kg	>5000 Rabbit	ECHA Dossier	
	inhalation (4 h) vapour	LC50 mg/l	28,1 mg/l Rat	ECHA Dossier	OECD Guideline 403
108-95-2	phenol; carbolic acid; monohydroxybenzene; phenylalcohol*				
	oral	LD50 mg/kg	282 mg/kg Mouse.	Horikawa 1975	
	dermal	LD50 mg/kg	660 mg/kg Rat	ECHA Dossier	OECD Guideline 402
	inhalation vapour	ATE mg/l	3 mg/l		
	inhalation dust/mist	LC50 mg/l	>0,9 (8h) Rat	ECHA Dossier	OECD Guideline 403



Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 12 of 22

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified:

In vitro mutagenicity/genotoxicity:

Method:

-OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

-OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

-OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Result: = negative ; Literature information: REACH Dossier

Chronic dermal toxicity :

Exposure time: ~546 d; Species: Mouse. ; Method: OECD Guideline 451

Result: Carcinogenicity = negative ; Literature information: REACH Dossier

Reproductive toxicity: :

Exposure route: oral. ; Species: Rat.

Method: OECD Guideline 421; Result: NOAEL >1000 mg/kg; Literature information: REACH Dossier

Developmental toxicity/teratogenicity :

Exposure route: dermal. ; Species: Rat.

Method: OECD Guideline 414 ; Result: NOAEL >2000 mg/kg; Literature information: REACH Dossier

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified:

Subacute inhalative toxicity : Method: -; Exposure time: 28d; Species: Rat; Results: NOAEL > 980

mg/m³; Literature information: J Appl Toxicol, Vol 11(4), pp 297-302; Subacute dermal toxicity: Method:

OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study); Exposure time: 28d; Species:

Rabbit; Results: NOAEL 1000 mg/kg(bw)/day; Literature information: REACH Dossier; Subchronic oral

toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents); Species: Rat;

Results: NOAEL = 125 mg/kg; Literature information: REACH Dossier

2,6-di-tert-butylphenol:

In vitro mutagenicity/genotoxicity:

Method:

-OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

-OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Result: negative ; Literature information: ECHA dossier

During animal experiments no indications of reproductive toxicity were observed. -Screening; Literature information: REACH Dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 13 of 22

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified:

Subchronic oral toxicity:

Exposure time: 90d; Species: Sprague-Dawley Rat.; Method: OECD Guideline 408; Result: LOAEL = 125 mg/kg; Literature information: REACH Dossier

Subacute inhalative toxicity :

Exposure time: 28d; Species: Sprague-Dawley Rat.; Result: NOAEC > 980 mg/m3; Literature information: REACH Dossier

Subacute dermal toxicity :

Exposure time: 28d; Species: Rabbit ; Method: OECD Guideline 410

Result: NOAEL 1000 mg/kg; Literature information: REACH Dossier

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified:

In vitro mutagenicity/genotoxicity:

Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay) with modifications

Results: negative / positive

Method: OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

Results: negative

Method: OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Results: negative / positive

Literature information: REACH Dossier

In vivo mutagenicity/genotoxicity

Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Results: negative ; Literature information: REACH Dossier

Reproductive toxicity

Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

Exposure time: 28d; Species: Rat

Results: NOAEL = > 2000 mg/kg(bw)/day; Literature information: REACH Dossier

Developmental toxicity/teratogenicity:

Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study)

Exposure time: 28d; Species: Rat

Results: NOAEL = > 2000 mg/kg(bw)/day; Literature information: REACH Dossier

2,6-di-tert-butylphenol:

Subchronic oral toxicity:

Exposure time: 90d; Species: Han Wistar Rat. ; Method: OECD Guideline 408

Result: NOAEL > 270 -298mg/kg; Literature information: REACH Dossier

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance (> 0,1 %) that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

Frequent contact specially if dried out may cause skin and eye irritations.

SECTION 12: Ecological information**12.1. Toxicity**



Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 14 of 22

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Wylan HV 15

Revision: 12.01.2026

Page 15 of 22

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Pimephales promelas	ECHA Dossier	
	Acute algae toxicity	ErC50 >100 mg/l	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	
	Acute crustacea toxicity	EC50 >10000 mg/l	48 h	Daphnia magna	ECHA Dossier	
	Crustacea toxicity	NOEC 10 mg/l	21 d	Daphnia magna	ECHA Dossier	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LC50 LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier	OECD Guideline 203
	Acute crustacea toxicity	EC50 EL50 >10000 mg/l	48 h	Daphnia magna (Big water flea)	ECHA Dossier	OECD Guideline 202
	Algae toxicity	NOEC NOEL > 100 mg/l	3 d	Pseudokirchneriella subcapitata	ECHA Dossier	
	Crustacea toxicity	NOEC NOEL > 10 mg/l	21 d	Daphnia magna (Big water flea)	ECHA Dossier	OECD Guideline 211
128-39-2	2,6-di-tert-butylphenol					
	Acute fish toxicity	LC50 1,4 mg/l	96 h	Pimephales promelas	ECHA Dossier	
	Acute algae toxicity	ErC50 1,4 mg/l	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	
	Acute crustacea toxicity	EC50 0,45 mg/l	48 h	Daphnia magna	ECHA Dossier	
	Fish toxicity	NOEC 0,053 mg/l	42 d	Oryzias latipes	ECHA Dossier	
	Crustacea toxicity	NOEC 0,023 mg/l	21 d	Daphnia magna	ECHA Dossier	
104-76-7	2-ethylhexan-1-ol*					
	Acute fish toxicity	LC50 17,1 mg/l	96 h	Leuciscus idus melanotus	ECHA Dossier	EU Method C.1
	Acute algae toxicity	ErC50 11,5 mg/l	72 h	Desmodesmus subspicatus	ECHA Dossier	EU Method C.3
	Acute crustacea toxicity	EC50 39 mg/l	48 h	Daphnia magna	ECHA Dossier	EU Method C.2
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*					
	Acute fish toxicity	LC50 >79 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier	EPA OTS 797.1400
	Acute algae toxicity	ErC50 >110 mg/l	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 69 mg/l	48 h	Daphnia magna	ECHA Dossier	EPA OTS 797.1300
	Fish toxicity	NOEC 9,4 mg/l	35 d	Brachydanio rerio	ECHA Dossier	
	Crustacea toxicity	NOEC 37 mg/l	21 d	Daphnia magna	ECHA Dossier	OECD Guideline 211
	Acute bacteria toxicity	EC50 100 mg/l ()		activated sludge	ECHA Dossier	OECD 301C
108-88-3	toluene*					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	ECHA Dossier	
	Acute crustacea toxicity	EC50 3,78 mg/l	48 h	Ceriodaphnia dubia	ECHA Dossier	US EPA 600/4-91-003

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 16 of 22

	Acute bacteria toxicity	EC50 ()	134 mg/l	3 h	Chlorella vulgaris and Chlamydomonas angulosa	ECHA Dossier	
108-95-2	phenol; carbolic acid; monohydroxybenzene; phenylalcohol*						
	Acute fish toxicity	LC50 mg/l	21,93	96 h	Poecilia reticulata	ECHA Dossier	
	Acute algae toxicity	ErC50	61,1 mg/l	96 h	Pseudokirchneriella subcapitata	ECHA Dossier	
	Acute crustacea toxicity	EC50	3,1 mg/l	48 h	Ceriodaphnia dubia	ECHA Dossier	
	Fish toxicity	NOEC mg/l	0,077	60 d	Cirrhina mrigala	ECHA Dossier	

12.2. Persistence and degradability

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

CAS No	Chemical name	Method	Value	d	Source
	Evaluation				
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C	2-4%	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).				
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	OECD Guideline 301 F	31%	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).				
128-39-2	2,6-di-tert-butylphenol	OECD 301C / ISO 9408 / EEC 92/69 annex V, C.4-F	4,5	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).				
104-76-7	2-ethylhexan-1-ol*	OECD 301C / ISO 9408 / EEC 92/69 annex V, C.4-F	>60%	14	ECHA Dossier
	Readily biodegradable (according to OECD criteria).				
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*	OECD 301C / ISO 9408 / EWG 92/69 Anhang V, C.4-F	94%	14	ECHA Dossier
	Readily biodegradable (according to OECD criteria).				
108-88-3	toluene*	WoE	>60%	28	ECHA Dossier
	Biodegradable.				
108-95-2	phenol; carbolic acid; monohydroxybenzene; phenylalcohol*	OECD Guideline 301 C	62	5	ECHA Dossier
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.



Safety Data Sheet

SRS Schmierstoff Vertrieb GmbH

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 17 of 22

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	> 3,5
128-39-2	2,6-di-tert-butylphenol	4,5
104-76-7	2-ethylhexan-1-ol*	2,9
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*	1,32
108-88-3	toluene*	2,73
108-95-2	phenol; carbolic acid; monohydroxybenzene; phenylalcohol*	1,47

BCF

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene*	90	Leuciscus idus melanotus	
108-95-2	phenol; carbolic acid; monohydroxybenzene; phenylalcohol*	17,5	Danio rerio	ECHA Dossier

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.7. Other adverse effects

No information available.

Further information

Ozone depletion potential (ODP): No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)



Safety Data Sheet

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 18 of 22

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
Inland waterways transport (ADN)	
<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
Marine transport (IMDG)	
<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
Air transport (ICAO-TI/IATA-DGR)	
<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
<u>14.5. Environmental hazards</u>	
ENVIRONMENTALLY HAZARDOUS:	No
<u>14.6. Special precautions for user</u>	
Informations for safe handling see chapter 7.	
Informations for personal protective equipment see chapter 8.	
<u>14.7. Maritime transport in bulk according to IMO instruments</u>	
not relevant	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2010/75/EU on industrial emissions:

No information available.

Directive 2004/42/EC on VOC in paints and varnishes:

No information available.

Information according to Directive 2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No (mixture): 3, 75

Observe in addition any national regulations!

National regulatory information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 19 of 22

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Regulation (EU) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals: not relevant

15.2 Chemical Safety Assessment
not applicable.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 15,16.

Rev. : 1,0 - 07.05.2015

Rev. : 1,1 - 01.02.2016

Rev. : 2,0 - 27.03.2017

Rev. : 3,0 - 29.03.2018

Rev. : 4,0 - 28.03.2019

Rev.: 5,0 - 31.03.2020 Changes in chapter: 1.2, 8.1, 10.3, 15.1, 16

Rev.: 5,1 - 23.07.2020 Changes in chapter: 9.1, 16

Rev.: 6,0 - 02.07.2021; Changes in chapter: 3.2, 6.1, 6.3, 11.2, 12.6, 12.7, 15.1, 16

Rev.: 7,0 - 29.07.2022, Changes in chapter: 2.3, 3.2, 8.1, 8.2, 11.1, 12.1, 12.1, 12.3, 12.5, 12.6, 16

Rev.: 8,0 - 01.07.2023, Changes in chapter: 8.1, 9.1, 10.1, 12.7, 16

Rev.: 8,1 - 06.11.2023, Changes in chapter: 3.2, 8.1, 9.1, 12.1, 12.2, 12.3, 16

Rev.: 8,2 - 10.01.2024, Changes in chapter: 1.4, 2.2, 12.5, 12.6, 16

Rev.: 9,0 - 22.01.2025, Changes in chapter: 16

Rev.: 10,0 - 12.01.2026, Changes in chapter: 15.1, 16

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 20 of 22

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
Acute Tox. 3: Acute toxicity, hazard category 3
Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Corr. 1B: Skin corrosion, sub-category 1B
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Irrit. 2: Eye irritation, hazard category 2
Skin Sens. 1: Skin sensitisation, hazard category 1
Muta. 2: Germ cell mutagenicity, hazard category 2
Repr. 2: Reproductive toxicity, hazard category 2
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS: Chemical Abstracts Service
CLP: Classification, Labelling and Packaging of substances and mixtures
d: day(s)
DNEL: Derived No Effect Level
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
ECHA: European Chemicals Agency
EWC: European Waste Catalogue
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
h: hour
LOAEL: Lowest observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level
NOAEC: No observed adverse effect concentration
NLP: No-Longer Polymers
NTP: National Toxicology Program
N/A: not applicable
OECD: Organisation for Economic Co-operation and Development
PNEC: predicted no effect concentration
PBT: Persistent bioaccumulative toxic
PMT: Persistent, mobile and toxic

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 21 of 22

REACH: Registration, Evaluation, Authorisation of Chemicals

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

SVHC: substance of very high concern

TRGS: Technische Regeln für Gefahrstoffe

UN: United Nations

TSCA: Toxic Substances Control Act

vPvM: very persistent and very mobile

vPvB: very persistent and very bioaccumulative

VOC: Volatile Organic Compounds

WGK: Water Hazard Class (Germany)

Key literature references and sources for data<https://echa.europa.eu/><https://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp><https://cfpub.epa.gov/ecotox/search.cfm><http://www.inchem.org/#/search><https://pubchem.ncbi.nlm.nih.gov/><http://ccinfoweb.ccohs.ca/rtecs/search.html><https://webrigoletto.uba.de/rigoletto/>**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008****[CLP]**

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method. ; H304: On basis of test data

Environmental hazards: Calculation method.

Physical hazards: On basis of test data

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SRS Wiolan HV 15

Revision: 12.01.2026

Page 22 of 22

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)