

according to Regulation (EC) No 1907/2006

### SRS Wiolan HVX 32

Revision date: 04.11.2024

Page 1 of 17

1.1. Product identifier		
SRS Wiolan HVX 32		
1.2. Relevant identified uses of th	e substance or mixture and uses advised against	
Use of the substance/mixture		
Hydraulic fluids		
Uses advised against		
none		
1.3. Details of the supplier of the	safety data sheet	
Company name:	SRS Schmierstoff Vertrieb GmbH	
Street:	Neuenkirchener Straße 8	
Place:	D-48497 Salzbergen	
Telephone:	05976 - 945-0	
Responsible Department:	Abt. Produktsicherheit: info.reach@srs-oil.de	
<u>1.4. Emergency telephone</u> number:	Gift-Informationszentrum Nord (Göttingen) - Telefon 0551-19240	

# 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

H412

#### Regulation (EC) No 1272/2008

### Hazard statements

Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

	-
P273	Avoid release to the environment.
P501	Dispose of contents/container to local/regional/national/international regulations.

### 2.3. Other hazards

This mixture contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH. For information or further instructions, see also section 11 or 12.

### **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

### **Relevant ingredients**

CAS No	Chemical name	Chemical name			
	EC No	Index No	REACH No		
	Classification (Regulation (EC) No	Classification (Regulation (EC) No 1272/2008)			
64742-56-9	-9 Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			50 - < 55 %	
	265-159-2	649-469-00-9	01-2119480132-48		
	Asp. Tox. 1; H304				
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			1 - < 3 %	
	265-158-7	649-468-00-3	01-2119487077-29		



according to Regulation (EC) No 1907/2006

### SRS Wiolan HVX 32

Revision date: 04.11.2024

Page 2 of 17

	Asp. Tox. 1; H304			
128-39-2	2,6-di-tert-butylphenol			0.2 - < 0.3 %
	204-884-0 01-2119490822-33			
	Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic 1; H315 H400 H410			
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*			< 0.1 %
	201-297-1 607-035-00-6 01-2119452498-28			
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			

### Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Cond	c. Limits, M-factors and ATE	
64742-56-9	265-159-2	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	50 - < 55 %
	inhalation: LC50 = >5,53 mg/l (dusts or mists); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg		
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	1 - < 3 %
	inhalation: LC50 = > 5,53 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
128-39-2	204-884-0	2,6-di-tert-butylphenol	0.2 - < 0.3 %
	dermal: LD50	0 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
80-62-6	201-297-1	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*	< 0.1 %
	inhalation: L0 LD50 = >500	C50 = 29,8 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: 0 mg/kg	

#### **Further Information**

\*Substance for which a community occupational exposure limit value applies in the European Union.

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London).

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

### After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, seek medical treatment.

### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or



according to Regulation (EC) No 1907/2006

### SRS Wiolan HVX 32

Revision date: 04.11.2024

if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed If swallowed or in the event of vomiting, risk of entering the lungs.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Sand. Foam. Carbon dioxide (CO2). Extinguishing powder. In case of major fire and large quantities: Water spray jet. Water mist.

#### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO2) Sulphur dioxide (SO2)

Nitrogen oxides (NOx)

### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Co-ordinate fire-fighting measures to the fire surroundings.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Ventilate affected area.

Special danger of slipping by leaking/spilling product.

### For non-emergency personnel

Wear personal protection equipment (refer to section 8).

### For emergency responders

No special precautionary measures are necessary.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil. If required, notify relevant authorities according to all applicable regulations.

### 6.3. Methods and material for containment and cleaning up

#### For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.


### 6.4. Reference to other sections

No information available.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Page 3 of 17





according to Regulation (EC) No 1907/2006

## SRS Wiolan HVX 32

Revision date: 04.11.2024

### Advice on safe handling

Wear suitable protective clothing. (See section 8.) Avoid formation of oil dust.

### Advice on protection against fire and explosion

Usual measures for fire prevention. Keep away from sources of ignition - No smoking. Fire class B

### Advice on general occupational hygiene

Clean skin thoroughly after working.

Do not put any product-impregnated cleaning rags into your trouser pockets.

### Further information on handling

Do not breathe vapour/aerosol. Avoid contact with eyes and skin. General protection and hygiene measures: See section 8.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

### Hints on joint storage

Do not store together with: Gas. Explosives. Oxidizing substances. Radioactive substances. Infectious substances

### Further information on storage conditions

Temperature control required. Protect from light. Keep container tightly closed. Do not allow contact with air.

### 7.3. Specific end use(s)

See section 1.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m³	fib/cm³	Category	Origin
80-62-6	Methyl methacrylate	50	-		TWA (8 h)	
		100	-		STEL (15 min)	

#### **DNEL/DMEL** values

CAS No	Name of agent	-	-	
DNEL type Exposure route Effect Value				
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Bas	seoil - unspecified		
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³
Worker DNEL,	long-term	inhalation	local	5,58 mg/m³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNE	EL, long-term	oral	systemic	0,74 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	local	1,19 mg/m³
64742-55-8	64742-55-8 Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			
Worker DNEL, long-term inhalation systemic 2,73 mg			2,73 mg/m³	
Worker DNEL,	long-term	inhalation	local	5,58 mg/m³

Page 4 of 17



according to Regulation (EC) No 1907/2006

### SRS Wiolan HVX 32

Revision date: 04.11.2024
---------------------------

Page 5 of 17

				i aye
Consumer DN	EL, long-term	oral	systemic	0,74 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>
128-39-2	2,6-di-tert-butylphenol			
Worker DNEL	, long-term	dermal	systemic	11,25 mg/kg bw/day
Worker DNEL	, long-term	inhalation	systemic	70,61 mg/m <sup>3</sup>
Consumer DN	EL, long-term	inhalation	systemic	20,9 mg/m <sup>3</sup>
Consumer DN	EL, long-term	oral	systemic	6,75 mg/kg bw/day
Consumer DN	EL, long-term	dermal	systemic	6,75 mg/kg bw/day
80-62-6	methyl methacrylate; methyl 2-methylprop	o-2-enoate; methyl 2-methylpropend	pate*	
Worker DNEL	, long-term	inhalation	local	208 mg/m <sup>3</sup>
Worker DNEL	, long-term	inhalation	systemic	348,4 mg/m <sup>3</sup>
Worker DNEL	, acute	inhalation	local	416 mg/m <sup>3</sup>
Worker DNEL	, long-term	dermal	systemic	13,67 mg/kg bw/day
Worker DNEL	, long-term	dermal	local	1,5 mg/cm <sup>2</sup>
Worker DNEL	, acute	dermal	local	1,5 mg/cm <sup>2</sup>
Consumer DN	EL, long-term	inhalation	systemic	74,3 mg/m <sup>3</sup>
Consumer DN	EL, long-term	inhalation	local	104 mg/m <sup>3</sup>
Consumer DN	EL, acute	inhalation	local	208 mg/m <sup>3</sup>
Consumer DN	EL, long-term	dermal	systemic	8,2 mg/kg bw/day
Consumer DN	EL, long-term	dermal	local	1,5 mg/cm <sup>2</sup>
Consumer DNEL, long-term		oral	systemic	8,2 mg/kg bw/day
Consumer DN	EL, acute	dermal	local	1,5 mg/cm <sup>2</sup>
PNEC values				-
CAS No	Name of agent			

Environmental compartment		Value	
64742-56-9	i6-9 Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified		
Secondary poisoning 9,33 mg/kg			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified		
Secondary po	isoning	9,33 mg/kg	
128-39-2	2,6-di-tert-butylphenol		
Freshwater		0.001 mg/l	
Freshwater (intermittent releases)		0.004 mg/l	
Marine water		0.0001 mg/l	
Freshwater se	ediment	0,317 mg/kg	
Marine sediment		0,0317	
Secondary poisoning		60 mg/kg	



Revision date: 04.11.2024

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## SRS Wiolan HVX 32

Page 6 of 17

Micro-organ	10 mg/l	
Soil		0,679 mg/kg
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*	
Freshwater		0,94 mg/l
Freshwater (intermittent releases)		0,94 mg/l
Marine water		0,094 mg/l
Freshwater sediment		10,2 mg/kg
Marine sediment		0,102 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		1,48 mg/kg

#### Additional advice on limit values

Air limit values: Possibility of exposure to Aerosol (Mineral oil ) Limit value (TLV-TWA ) = 5 mg/ m3 - Source: ACGIH Limit value (TLV-STEL ) = 10 mg/ m3 - Source: ACGIH

STEL: short-term exposure limits TLV: Threshold Limiting Value TWA: time weighted average ACGIH:American Conference of Governmental Industrial Hygienists

### 8.2. Exposure controls



### Appropriate engineering controls

Provide adequate ventilation.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Safety goggles with side protection. In case of increased risk add protective face shield. EN 166

### Hand protection

Use safety gloves of following materials: NBR (nitrile) / neopren / viton (permeationslevel 5 - 6), Cat. II according to norm EN 374/EN 388.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Gloves must be periodically inspected and changed in case of wear, perforations or contaminations. In the case of wanting to use the gloves again, clean them before taking off and air them well.

#### Skin protection

Oil-resistant and hardly inflammable protective clothing.

### **Respiratory protection**

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:


-aerosol or mist formation

-Exceeding exposure limit values

Suitable respiratory protection apparatus: Respiratory equipment in case of nebulosity or aerosol: Use a mask with a filter type A2, A2/P2 or ABEK.

The filter class must be suitable for the maximum contaminant concentration





Page 7 of 17



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

### SRS Wiolan HVX 32

Revision date: 04.11.2024

(gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

# Environmental exposure controls

No information available.

### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

9.1. Information on basic physical and ch Physical state:	Liquid		
Colour:	clear		
Odour:	characteristic		
			Test method
Melting point/freezing point:		No information available.	
Boiling point or initial boiling point and		No information available.	
boiling range:			
Flammability:		No information available.	
Lower explosion limits:		No information available.	
Upper explosion limits:		No information available.	
Flash point:		212 °C	
Auto-ignition temperature:		No information available.	
Decomposition temperature:		No information available.	
pH-Value:		No information available.	
Viscosity / kinematic:		32,12 mm²/s	DIN EN ISO 3104
(at 40 °C)			
Water solubility:		No information available.	
Solubility in other solvents			
No information available.			
Partition coefficient n-octanol/water:		No information available.	
Vapour pressure:		No information available.	
(at 20 °C)			
Vapour pressure:		No information available.	
(at 50 °C)			DIN 64767
Density (at 15 °C):		0,869 g/cm <sup>3</sup> No information available.	DIN 51757
Bulk density:			
Relative vapour density:		No information available.	
Particle characteristics:		No information available.	
9.2. Other information			
Information with regard to physical ha	azard classes		
Explosive properties			
none			
Sustaining combustion:		No data available	
Self-ignition temperature			
Solid:		No information available.	
Gas:		No information available.	
Oxidizing properties			
none			
Other safety characteristics		<b>.</b>	
Evaporation rate:		No information available.	
Solvent separation test:		No information available.	
Solvent content:		No information available.	
Solid content:		No information available.	
Sublimation point:		No information available.	



according to Regulation (EC) No 1907/2006

### **SRS Wiolan HVX 32**

Revision date: 04.11.2024

Page 8 of 17

Softening point:	No information available.
Pour point:	-30 °C
Viscosity / dynamic:	No information available.
Flow time:	No information available.

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

# 10.3. Possibility of hazardous reactions

No hazardous reactions known.

Refer to chapter 10.5.

# 10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Toxicocinetics, metabolism and distribution

No information available.

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
64742-56-9	Distillates (petroleum)	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified							
	oral	LD50 mg/kg	>5000	Rat.	ECHA Dossier				
	dermal	LD50 mg/kg	>5000	Rabbit.	ECHA Dossier				
	inhalation (4 h) dust/mist	LC50 mg/l	>5,53	Rat.	ECHA Dossier				
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified								
	oral	LD50 mg/kg	> 5000	Rat	ECHA Dossier	OECD Guideline 401			
	dermal	LD50 mg/kg	> 2000	Rabbit	ECHA Dossier	OECD Guideline 402			
	inhalation (4 h) dust/mist	LC50 mg/l	> 5,53	Rat	ECHA Dossier	OECD Guideline 403			
128-39-2	2,6-di-tert-butylphenol								



according to Regulation (EC) No 1907/2006

### SRS Wiolan HVX 32

Revision date: 04.11.2024

Page 9 of 17

	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier	OECD 401
	dermal	LD50 mg/kg	>2000	Rat	ECHA Dossier	
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*					
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier	WoE
	dermal	LD50 mg/kg	> 5000	Rabbit	ECHA Dossier	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 mg/l	29,8	Rat	ECHA Dossier	

### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met. Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified: In vitro mutagenicity/genotoxicity: Method: -OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) -OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) -OECD Guideline 471 (Bacterial Reverse Mutation Assay) Result: = negative ;Literature information: REACH Dossier

Exposure time: ~546 d; Species: Mouse. Method: OECD Guideline 451 Result: Carcinogenicity = negative ; Literature information: REACH Dossier

Reproductive toxicity: : Exposure route: oral.; Species: Rat. Method: OECD Guideline 421 Result: NOAEL >1000 mg/kg; Literature information: REACH Dossier

Developmental toxicity/teratogenicity : Exposure route: dermal. ; Species: Rat. Method: OECD Guideline 414 Result: NOAEL >2000 mg/kg; Literature information: REACH Dossier

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified: In vitro mutagenicity/genotoxicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay) with modifications Results: negative / positive Method: OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) Results: negative Method: OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) Results: negative / positive Literature information: REACH Dossier



according to Regulation (EC) No 1907/2006

### SRS Wiolan HVX 32


Revision date: 04.11.2024

Page 10 of 17

In vivo mutagenicity/genotoxicity Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) Results: negative ; Literature information: REACH Dossier Reproductive toxicity Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test) Exposure time: 28d; Species: Rat Results: NOAEL = > 2000 mg/kg(bw)/day; Literature information: REACH Dossier Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study) Exposure time: 28d: Species: Rat Results: NOAEL = > 2000 mg/kg(bw)/day; Literature information: REACH Dossier 2,6-di-tert-butylphenol: In vitro mutagenicity/genotoxicity: Method: OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test), OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test); Result: negative Literature information: REACH Dossier: During animal experiments no indications of reproductive toxicity were observed. -Screening; Literature information: REACH Dossier methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate: In vitro mutagenicity/genotoxicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay) Result: negative Literature information: REACH Dossier Carcinogenicity: Species: Rat (Fischer 344) Method: OECD Guideline 451 (Carcinogenicity Studies) Result: negative (NOAEC >= 2,05 mg/l); Literature information: REACH Dossier Reproductive toxicity: Species: Rat (Wistar) Method: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study) Result: NOAEL = 400 mg/kg; Literature information: REACH Dossier Developmental toxicity/teratogenicity: Species: Rabbit. Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study) Result: NOAEL = 450 mg/kg; Literature information: REACH Dossier STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified: Subchronic oral toxicity: Exposure time: 90d; Species: Sprague-Dawley Rat. Method: OECD Guideline 408 Result: LOAEL = 125 mg/kg; Literature information: REACH Dossier Subacute inhalative toxicity : Exposure time: 28d; Species: Sprague-Dawley Rat. Result: NOAEC > 980 mg/m3; Literature information: REACH Dossier

Subacute dermal toxicity : Exposure time: 28d; Species: Rabbit Method: OECD Guideline 410 Result: NOAEL = 1000 mg/kg; Literature information: REACH Dossier

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified:





according to Regulation (EC) No 1907/2006

### SRS Wiolan HVX 32

Revision date: 04.11.2024

Page 11 of 17

Subacute inhalative toxicity : Method: -; Exposure time: 28d; Species: Rat; Results: NOAEL > 980 mg/m3; Literature information: J Appl Toxicol, Vol 11(4), pp 297-302; Subacute dermal toxicity: Method: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study); Exposure time: 28d; Species: Rabbit; Results: NOAEL 1000 mg/kg(bw)/day; Literature information: REACH Dossier; Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents); Species: Rat; Results: NOAEL = 125 mg/kg; Literature information: REACH Dossier

### 2,6-di-tert-butylphenol:

Subchronic oral toxicity: Method: OECD Guideline 408; Species: Han Wistar Rat.; Exposure time: 90d. Result: NOAEL > 270 -298mg/kg; Literature information: REACH Dossier

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate: Chronic oral toxicity: Method: - ; Species: Rat (Wistar) Results: NOAEL >= 2000 ppm; Literature information: REACH Dossier

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

### Endocrine disrupting properties

This product does not contain a substance (> 0,1 %) that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### Other information

Frequently or prolonged contact with skin may cause dermal irritation.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d	Species	Source	Method	
64742-56- 9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified							
	Acute fish toxicity	LC50 mg/l	>100	96 h	Pimephales promelas	ECHA Dossier		
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Pseudokirchnerella subcapitata	ECHA Dossier		
	Acute crustacea toxicity	EC50 mg/l	>10000	48 h	Daphnia magna	ECHA Dossier		
	Crustacea toxicity	NOEC	10 mg/l	21 d	Daphnia magna	ECHA Dossier		
64742-55- 8	Distillates (petroleum),	hydrotreated li	ght paraffinio	; Baseoi	I - unspecified			
	Acute fish toxicity	LC50 100 mg/l	LL50 >	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier	OECD Guideline 203	
	Acute crustacea toxicity	EC50 >10000 m	EL50 g/l	48 h	Daphnia magna (Big water flea)	ECHA Dossier	OECD Guideline 202	
	Algae toxicity	NOEC 100 mg/l	NOEL >	3 d	Pseudokirchneriella subcapitata	ECHA Dossier		
	Crustacea toxicity	NOEC 10 mg/l	NOEL >	21 d	Daphnia magna (Big water flea)	ECHA Dossier	OECD Guideline 211	
128-39-2	2,6-di-tert-butylphenol							



# according to Regulation (EC) No 1907/2006

### **SRS Wiolan HVX 32**

Revision date: 04.11.2024

Page 12 of 17

				•				
	Acute fish toxicity	LC50	1,4 mg/l	96 h	Pimephales promelas	ECHA Dossier		
	Acute algae toxicity	ErC50	1,4 mg/l		Pseudokirchnerella subcapitata	ECHA Dossier		
	Acute crustacea toxicity	EC50 mg/l	0,45	48 h	daphnia magna	ECHA Dossier		
	Fish toxicity	NOEC mg/l	0,053	42 d	Oryzias latipes	ECHA Dossier		
	Crustacea toxicity	NOEC mg/l	0,023	21 d	Daphnia magna	ECHA Dossier		
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*							
	Acute fish toxicity	LC50 mg/l	>79		Oncorhynchus mykiss	ECHA Dossier	EPA OTS 797.1400	
	Acute algae toxicity	ErC50 mg/l	>110		Pseudokirchnerella subcapitata	ECHA Dossier	OECD Guideline 201	
	Acute crustacea toxicity	EC50	69 mg/l	48 h	Daphnia magna	ECHA Dossier	EPA OTS 797.1300	
	Fish toxicity	NOEC	9,4 mg/l	35 d	Brachydanio rerio	ECHA Dossier		
	Crustacea toxicity	NOEC	37 mg/l	21 d	Daphnia magna	ECHA Dossier	OECD Guideline 211	
	Acute bacteria toxicity	EC50 mg/l()	100		activated sludge	ECHA Dossier	OECD 301C	

### 12.2. Persistence and degradability

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

CAS No	Chemical name							
	Method	Value	d	Source				
	Evaluation		·	·				
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; B	aseoil - unspecified						
	OECD 301B / ISO 9439 / EEC 92/69 annex V,	2-4%	28	ECHA Dossier				
	C.4-C							
	Not easily bio-degradable (according to OECD-criteria)	).						
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified							
	OECD Guideline 301 F	31%	28	ECHA Dossier				
	Not easily bio-degradable (according to OECD-criteria).							
128-39-2	2,6-di-tert-butylphenol							
	OECD 301C / ISO 9408 / EEC 92/69 annex V,	4,5	28	ECHA Dossier				
	Not easily bio-degradable (according to OECD-criteria)	).						
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*							
	OECD 301C / ISO 9408 / EWG 92/69 Anhang	94%	14	ECHA Dossier				
	V, C.4-F							
	Readily biodegradable (according to OECD criteria).							

### 12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

# Partition coefficient n-octanol/water Chemical name

CAS No

Log Pow



Revision date: 04.11.2024

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

### SRS Wiolan HVX 32

Page 13 of 17

64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	> 3,5
128-39-2	2,6-di-tert-butylphenol	4,5
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate*	1,32

#### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

### 12.7. Other adverse effects

No information available.

#### **Further information**

Ozone depletion potential (ODP): No information available.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

#### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

### **SECTION 14: Transport information**

Land transport (ADR/RID)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 9006
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es):	9
14.4. Packing group:	-
Hazard label:	-
Classification code:	M12
Marine transport (IMDG)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.



### according to Regulation (EC) No 1907/2006

	SRS Wiolan HVX 32	
Revision date: 04.11.2024		Page 14 of 17
<u>14.3. Transport hazard class(es):</u> 14.4. Packing group:	No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for userInformations for safe handling see chInformations for personal protective of14.7. Maritime transport in bulk accordingnot relevant	equipment see chapter 8.	
SECTION 15: Regulatory information		
15.1 Safety health and environmental rec	gulations/legislation specific for the substance or mixture	
EU regulatory information		
Restrictions on use (REACH, annex XVI Entry 3, Entry 75	I):	
Directive 2010/75/EU on industrial emissions:	No information available.	
Directive 2004/42/EC on VOC in paints and varnishes:	No information available.	
Information according to Directive 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)	
Additional information		
	, ,	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).	
Water hazard class (D): Additional information	1 - slightly hazardous to water	
Regulation (EU) No. 649/2012 of the import of dangerous chemicals: not r	European parliament and of the council concerning the export and elevant	
15.2 Chemical Safety Assessment not applicable.		
SECTION 16: Other information		
Changes This data sheet contains changes fro Rev. : 1,0 - 28.11.2016 Rev. : 2.0 - 27.11.2017	om the previous version in section(s): 11,15,16.	

Rev. : 2,0 - 27.11.2017 Rev. : 3,0 - 27.11.2018 Rev. : 4,0 - 29.11.2019, Changes in chapter: 1.2, 8.1, 10.3 , 15.1, 16



according to Regulation (EC) No 1907/2006

### SRS Wiolan HVX 32

Page 15 of 17

Revision date: 04.11.2024


Rev. : 5,0 - 19.11.2020, Changes in chapter: 15.1, 16

Rev.: 6,0 - 22.11.2021, Changes in chapter: 3.2, 6.1, 6.3, 8.1, 11.1, 11.2, 12.1, 12.2, 12.3, 12.6, 12.7, 15.1, 16

Rev.: 7.0 - 21.11.2022, Changes in chapter: 2.3, 3.2, 8.1, 11.1, 12.1, 12.2, 12.3, 12.5, 12.6, 15.1 16

Rev.: 8.0 - 13.11.2023, Changes in chapter: 8.1, 9.1, 11.2, 12.1, 12.7, 14, 16

Rev.: 9.0 - 04.11.2023, Changes in chapter: 11.1, 12.1, 16



Page 16 of 17




# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## SRS Wiolan HVX 32

Revision date: 04.11.2024

Abbreviations and acronyms Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Skin Sens: Skin sensitisation STOT SE: Specific target organ toxicity - single exposure Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) CAS: Chemical Abstracts Service CLP: Classification, Labelling and Packaging of substances and mixtures d: day(s) DNEL: Derived No Effect Level IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European LIst of Notified Chemical Substances ECHA: European Chemicals Agency EWC: European Waste Catalogue IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany) h: hour LOAEL: Lowest observed adverse effect level LOAEC: Lowest observed adverse effect concentration LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NOAEL: No observed adverse effect level NOAEC: No observed adverse effect concentration NLP: No-Longer Polymers NTP: National Toxicology Program N/A: not applicable OECD: Organisation for Economic Co-operation and Development PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic PMT: Persistent, mobile and toxic REACH: Registration, Evaluation, Authorisation of Chemicals RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) SVHC: substance of very high concern TRGS: Technische Regeln für Gefahrstoffe **UN: United Nations** TSCA: Toxic Substances Control Act vPvM: very persistent and very mobile vPvB: very persistent and very bioaccumulative VOC: Volatile Organic Compounds WGK: Water Hazard Class (Germany) Key literature references and sources for data https://echa.europa.eu/ https://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp





according to Regulation (EC) No 1907/2006

## SRS Wiolan HVX 32

Revision date: 04.11.2024

Page 17 of 17

https://cfpub.epa.gov/ecotox/search.cfm http://www.inchem.org/#/search https://pubchem.ncbi.nlm.nih.gov/ http://ccinfoweb.ccohs.ca/rtecs/search.html https://webrigoletto.uba.de/rigoletto/

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008

#### [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### **Further Information**

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)